**Full-Size** PullOut™ Plans

# opular Woodworking

Nostalgic Poplar Porch Swing-Full Size Plans Make it Easy *p.41* 



**Build a Collector's Coffee Table-**Bring Your Memories to Life p.26






NOW ONLY \$3.95 US, \$4.95 CAN





**Build This Colonial Wall Cupboard-**Your Table Saw Does It All.



# Popular Woodworking



# at projects

**Full-size plans** 

**Dimensioned drawings** 

delivered to your door!

Subscribe to *Popular Woodworking* and get 6 bimonthly issues packed with projects — at least 7 per issue!

Each project comes with a complete cutting list and step-by-step instructions. And some include full-size PullOut™ Plans so you can start building right away.

You'll also get plenty of expert advice on tools, wood types, timesaving tricks, finishing techniques and more.

# SAVE 18% OFF THE NEWSSTAND PRICE

Mail the coupon below to get all this delivered to your door at the introductory rate of just \$19.97, a 16% savings off the newsstand rate! Subscribe to *Popular Woodworking* today.



**Furniture** 



Start my subscription to Popular Woodworking now at a savings of 16% off the newsstand rate. I pay just \$19.97 for 6 project-packed issues.

☐ Payment enclosed ☐ Bill me

M0895PW

Clip & mail to:

Popular Woodworking

PO Box 5369 Harlan, IA 51593-0869


Name\_\_\_\_\_

Address \_\_\_\_\_

City/State/Zip \_\_\_\_\_


Add \$6 for Canadian and other foreign subscriptions.

If you prefer not to cut cover, please see extra coupon on page 60.



# Contents







| - |     |      |     | - |     |      |
|---|-----|------|-----|---|-----|------|
| 0 | 979 | # In | 10  |   | 01  | 101  |
|   | 11  | 4.81 | 100 | • | C/H | / [[ |

| Classic Country Wall Cupboard by Steve Shanesy    | 22 |
|---|----|
| A table saw and hand tools will get the job done. |    |
| Collector's Coffee Table by Steve Shanesy         | 26 |
|   |    |

# **Technique**

| Turnings on the Table Saw by Don Kinneman                  | 30 |
|--|----|
| If you're "lathe-less," let your table saw do the turning! |    |

# PullOut Plans™

| Porch Swing by Steve Shanesy & David Thiel           |
|--|
| A few doweled joints, two mortise and tenons and our |
| full size patterns make this project easy.           |

# Snap Shop NEW

| CD Rack by Bruce Woods                                | 46 |
|---|----|
| A six-piece project to try your hand at form bending. |    |

# **Spindle Turning Basics** by Tobias Kaye 48 Step-by-step lathe lessons from an English Master Turner.

# Tool Review

| Chisels    | & Gouge      | es Round-up       | by Hugh Foster     |
|------------|--------------|-------------------|--------------------|
| Consider t | hese cutting | g edge evaluation | ns before you buy. |

# Columns & Departments

| Turnings            |  |  |  |  |  |  | 2         |
|---------------------|--|--|--|--|--|--|-----------|
| Letters             |  |  |  |  |  |  | 3         |
| Tricks of the Trade |  |  |  |  |  |  | 6         |
| Finishing Forum     |  |  |  |  |  |  | 8         |
| Business End        |  |  |  |  |  |  | 10        |
| Tried & True        |  |  |  |  |  |  | 16        |
| Cris Cuts           |  |  |  |  |  |  | 58        |
| Calendar            |  |  |  |  |  |  | 61        |
| News and Notes      |  |  |  |  |  |  | 62        |
| Resource Directory  |  |  |  |  |  |  | 64        |
| Wood Types          |  |  |  |  |  |  | 66        |
| Cartoon Contest     |  |  |  |  |  |  | 68        |
| Classifieds         |  |  |  |  |  |  | 69        |
| Out of the Woodwork |  |  |  |  |  |  | <i>72</i> |

# On the Cover

Our main cover project this month is a country wall cupboard from the U.S. Colonial period. One great feature is that it can be built using only a table saw and basic hand tools. Other projects on the cover include a Porch Swing that looks so good it will stop traffic on your street, a Collectors Coffee Table for showing off your treasures in great style, and a CD Rack that you won't find on any store shelf. All these projects require a minimum of equipment yet offer you classic looking furniture and accessories. PHOTO BY RON FORTH PHOTOGRAPHY

#### **Safety Note**

Safety is your responsibility. Manufacturers place safety devices on their equipment for a reason. In most photos you see in Popular Woodworking, these have been removed to provide clarity. In some cases we'll use an awkward body position so you can better see what's being demonstrated. Don't copy us. Think about each procedure you're going to perform beforehand. Think ahead. Safety First!

41

54

# Popular Woodworking®

Editor Stephen Shanesy Assistant Editor Victoria Stone Associate Editor David Thiel Art Director Scott Finke Production Artist Amy Schneider Technical Artist Bob Shreve

Contributing Editors: Graham Blackburn, R.J. De Cristoforo, Hugh Foster, Don Kinnaman, Ken Textor, Tom Wisshack

> Publisher Jeffry M. Lapin Editorial Director Bruce Woods

#### Circulation

David Lee, Dir. - Amanda Schuster, Mgr. Single Copy Sales Vicki Keaton

#### **Production**

Barbara Schmitz, Director Martha Wallace, Manager Kathi Howard, Assistant Sharon Lee, Composition Manager Ruth Preston, Art Production Manager

#### Advertising

Advertising Sales Manager Leslie Winters 25 Lewis St., Greenwich, CT 06830 Tel. (203)661-0515; Fax (203) 661-0519 Publisher's Representative

Bill Warren, Buchmayr Associates 137 Rowayton Ave., Rowayton, CT 06853 Tel. (203)855-8834; Fax (203)855-9138

Advertising Production Coordinator Kathy Georg - Tel. (513)531-2690, ext. 380

**Advertising Sales** Cathy Roll - Tel. (800)283-0963, ext. 315

# **Subscription Information**

Tel. (515) 280-1721

Popular Woodworking (ISSN 0884-8823, USPS 752-250) is published six times a year in January, March, May, July, September and November by F&W Publications, Inc. Editorial and advertising offices are located at 1507 Dana Ave., Cincinnati, OH 45207; tel.: (513)531-2222. Unsolicited manuscripts, photographs and artwork should include ample postage on a selfaddressed, stamped envelope (SASE); otherwise they will not be returned. Subscription rates: A year's subscription (6 issues) is \$19.97; outside of U.S.A. add \$7/year. Send all subscription inquiries, orders and address changes to: Popular Woodworking, P.O. Box 5369, Harlan, IA 51593 or call (515) 280-1721. Please allow 6 to 8 weeks for delivery. Copyright © 1995 by Popular Woodworking. Second-class postage paid at Cincinnati, Ohio, and additional mailing offices. Postmaster: Send all address changes to Popular Woodworking, P.O. Box 5369, Harlan, IA 51593. F&W Publications, Inc. officers: President: Richard Rosenthal; Senior Vice Presidents: Wm. Budge Wallis, Book Division; David R. Luppert, Finance and Administration; Vice President: Jeffry M. Lapin, Magazine/ Educational Services Division; Corporate Managers: Mert Ransdell, Book Division; Michael Patton Hoover, Manufacturing. Vol. 15, No. 2. Canada GST Reg. # R122594716

#### Produced and printed in the U.S.A.

#### **Attention Retailers:**

To carry Popular Woodworking in your store, call (800)786-6138, or write: Retail Services, F&W Publications, Inc., P.O. Box 601, Mt. Morris, IL 61054.

Woodworker's Book Club: 1507 Dana Ave., Cincinnati, OH 45207; (513)531-8250


# Turnings

e had a great time a few weeks back hosting a group of 50 readers and representatives of Freud, USA. The occasion was a seminar Popular Woodworking sponsored.

Before dinner, readers toured our Popular Woodworking workshop. A lively and informative seminar followed with Freud's Jim Brewer and Hugh Foster (yes, the same Hugh Foster that you've been reading in Popular Woodworking for years is a Freud spokesperson). Four subjects near and dear to us all were presented: saw blades and some genuine innovations that we'll all benefit from; the lowdown on "anti-kickback technology;" some important reminders about safety; and, a discussion and demonstration about plate or biscuit joinery.

Not being totally up to speed with "anti-kickback technology," I was surprised to learn the design of blades and other tooling with this feature is the legal safety standard of the German government and has been adopted throughout central and western Europe. Its purpose is to help protect industrial woodworkers. Freud was first to bring this technology to the U.S. and has offered it to us with no increase in prices! When you learn about how it works and why it works, it's an impressive presentation. What makes it a fascinating safety concept is that it is "passive" in nature. You, the woodworker, need do nothing to benefit from it (besides buy the tool to begin with). Unlike guards on machines (too many of which are never installed or too frequently removed at the peril of the operator), this safety feature does not affect the tool performance or the operation of equipment. In a future issue of Popular Woodworking, we will present this important innovation in more detail.

Freud's Mr. Brewer also enlightened us on new developments in saw blade design and presented a refresher course in saw blade selection. Important information to pass along includes the advantages of thin kerf blades. The main purpose is not to save an incidental amount of material on each cut, but to make your underpowered table saw perform better. Freud's tech department believes a 10" table saw using a standard 1/4" kerf



Popular Woodworking guests Rene Sterchi (l.) and John Hehn (c.), yuk it up with yours truly (r.) in the shop before dinner and the Freud seminar.

blade should be at least 3 h.p. or it is underpowered. The thin kerf blade requires less power from the motor. Sure, it's good for your motor, but it's also good for you since the stock, especially heavier stock being ripped, is easier to push through. Other important developments include blade design resulting in substantial noise reduction (Oh, how I hate those blades that scream), and a host of blade tooth designs for specific cutting operations.

Hugh Foster addressed shop safety concerns and reminded us that a pair of safety glasses (under \$20) could save our eye sight, and disposable foam ear plugs (25 cents) will help keep the hearing aid salesman away from our door (and savings account). Hugh also stayed late to discuss and demonstrate biscuit joinery with about half the crowd who decided the 9 p.m. scheduled ending was just too early to go home.

In future seminars, we'll bring the industry leaders to you, in person if you're one of the lucky ones who can attend, or vicariously through the pages of Popular Woodworking.

# A 'Snappy' New Feature

We're beginning a new feature this month called "Snap Shop." We'll be presenting simpler projects or techniques that can easily be demonstrated in pictures. If a picture's worth a thousand words, this first "Snap Shop" saved 14,000 words, or half a magazine! It's another way we're trying to get more information you can use between the covers of Popular Woodworking.

Styll Shaw

# Letters

Te welcome your comments, pro or con, about articles we publish. We also want to see color pictures of what you're building. Send your letters and photos to: Letters, Popular Woodworking, 1507 Dana Ave., Cincinnati, OH 45207. Letters may be edited for publication.

# **Woodworking World**

Thanks to all the readers who responded to our call for information about stagecoach plans in the July issue. You've provided plenty of sources for more infomation, and we appreciate the help!

I have used drawings and other plans for wagon wheels from Windy Hill Woods (P.O. Box 308, Central City, Iowa 52214). They have great drawings and photos and wheels that require no special tools to construct. Their prices are reasonable, too.

> Elmer F. Grissel Cedar Rapids, Iowa

For stagecoach building plans, I suggest readers write Kayo Fraser (c/o Northwest Enterprises, 161 Gold Creek Rd., Gold Creek, MT 59733) and request a catalog, which costs \$2. Not only do they have plans, but several good books such as The How-To Book of Stagecoach Building.

In addition, if anyone wants a list of manufacturers, suppliers and services for wagon and buggy parts, they should write to request The Reach (P.O. Box 932, Kendallville, IN 46775). The source book costs \$7.

> Mark Meccage Baker, Montana

If folks are looking for plans to build wagon wheels, they should write to Wildwood Designs (Box 661, Richland Center, WI 53581). Request plan #1103, which sells for \$2.50.

> David Nusbaum Pahrump, Nevada

# It's Greek, er Latin, to Us

Just a short note concerning your usage of common and scientific names of tree species. In your March issue (#83) you featured yellow-poplar in your Wood Types column. You refer to it as "yellow poplar" rather than as "yellow-poplar." The hyphen may appear to be trivial, but it is technically correct to use it when the species in questions is not a true member of the referenced genus.

Your scientific names in the article are also incorrectly handled. A scientific name is always italicized, or at least underlined. Furthermore, the genus is always capitalized, whereas the species is always in lowercase. Therefore, "liriotulipfera" dendron should "Liriodendron tulipifera" (note the misspelling of the species). Also "populus deltoidus" should be "Populus deltoides," and "populus balasamifera" should be "Populus balsamifera."

These discrepancies detract only marginally from an otherwise fine article. I enjoyed the information, as I do your magazine in general. However, as a forestry professor, I cannot help but correct such errors when I see them. It drives my students nuts!

> Michael G. Messina Bryan, Texas

# **OOPS**

I have just finished reading "An Elegant Plant Stand" in the March issue (#83) and without checking the plans completely, there are several errors.

First, the lower spindle tuming adds up to 10%", not 10%". Second, the upper spindle turning adds up to 7%", not 71/2". Third, the cross section A-A shows 41/4". It should be 21/4". Lastly, if you mean to show the drilling holes for the lower spindles on the drawer section lower triangle, the 11/4" dimension just won't cut it. That triangle is 1" smaller, therefore the dimensions cannot be the same.

> W.E. Gallagher Hot Springs Village, Arkansas


ED. Mr. Gallagher, you could have included a towel for wiping the egg off our faces!

# **More Preparing Stock**

I was browsing through the woodworking magazines at the local newsstand when I spotted the March, 1995



Circle #111 on Resource Directory Coupon



Circle #110 on Resource Directory Coupon

# Woodworkers-**Turn Your Craft Into CASH!**

The Woodworker's Guide to Pricing Your Work


- can help you turn your hobby into profit. You'll learn how to determine YOUR the dollar value for WORK your woodworking skills, estimate material costs per project, manage a budget, market

your work at craft fairs and through retailers, and develop the right business image and marketing plan. Sample business forms and planning sheets included will start you on your way.

#70268/\$18.99/160 pgs, paperback

# Make Your Woodworking Pay for Itself

income from what you love to do --woodworking! You'll discover thousands of ideas for things to make and sell, practical advice on where to sell your work and how to price it, and ways to cut costs on supplies



and tools. Plus, get tips to help you with keeping records, money management, filing taxes...All the information you need to make your woodworking pay for itself. #10323/\$16.99/128 pgs, paperback

# **30 DAY MONEY-BACK GUARANTEE!**

YES! Please send me the following books:

| DOOK #  | rrice o             |
|---|---------------------|
| Book #  | Price \$            |
| Sub<br>Add \$3.50 postage and handling<br>and \$1.00 for each additional bo<br>add 5.5% sales tax. Payment mu | ook. Ohio residents |
| ,   | Total \$            |
| VISA/MASTERCAR  | D ORDERS            |
| CALL TOLL-FREE 1-80   | 0-289-0963          |
| Payment enclosed \$   | (or)                |
| Charge my $\square$ Visa $\square$ MasterCa   | rd Exp.Date         |
| Acct. #   |                     |
| Signature   |                     |
| Name  |                     |
| Address   |                     |
| City  |                     |
| State   |                     |
| Allow 30 days for delive  | ery. 3186           |

# Letters

Popular Woodworking. The featured article, "Preparing Stock" by Hugh Foster, is just what I have been trying to get some information about.

The reason I was so interested in the article is because with my limited budget, I can't afford to buy much finished lumber. Locally, rough sawn lumber costs about half of finished lumber. I have plenty of time, so I don't mind making my own finished boards.

I have been trying to learn how to make finished stock from rough sawn, so I was excited about your article. Since I have a 6" jointer, I suppose the widest boards I should buy rough sawn is 6". The article, however, did not explain fully what is the longest board that can be surfaced on a jointer. My jointer has a total length of infeed and outfeed tables of about 42". Would it be possible to plane longer boards if I could construct an auxiliary infeed table? Also, can I expect that the rough sawn lumber I buy should be straight enough so that I can finish long boards?

When surfacing a bowed board on the jointer, should I maintain pressure on the outfeed table so I don't bend the cupped suction down to the infeed table and take as many passes as necessary to make one side flat? I am interested in learning more. Can you lead me to any other articles, books or sources on this subject?

> Frank G. Mungo Cuyahoga Falls, Ohio

ED. It's a pretty in-depth topic to handle here, but: yes, your widest board will be limited by the width of your jointer. As to length of board, as long as you keep the board flat to the outfeed table your only concern is awkwardness. Seldom will you need to use a board longer than 8', so determine your finished dimension and allow some overage for sniping and cracks. Don't count on straight boards from your lumber yard. Allow enough thickness to compensate for twist and bow. Long boards are a challenge, but if they aren't too bowed or twisted, you'll straighten them out. Some practice will aive you the feel for this chore. That leads to your last question: when surfacing a board, the goal is to have one surface finish flat. If you bend or force the board to meet the outfeed table you defeat that process. Make as many passes as it takes and your work will be the better for your patience.



# Giddy-Up

I have enjoyed the good articles in Popular Woodworking, and in the September, 1993 issue (#74), an article caught my eye, and amazingly, my memory. My daughter has a few horses and I thought the Exotic Western Stirrups by Devore O. Burch would be a great Christmas present. It was and she loves them.

> Stuart P. Jackson Roanoke, Virginia



Wudworker@AOL.COM.

#### **Email us!**

On CompuServe, contact us at Bruce Woods, 75463,3377, or leave a message in the Woodworking Section of the CompuServe Crafts Forum.

Our American Online screen name is Wudworker. To leave us a message without

using the mail system, look for the Exchange's Woodworking Center. Those of you on another online service can write to us at

Send to: Betterway Books

1507 Dana Avenue • Cincinnati, Ohio 45207

# MILCS

# MAKE BEAUTIFUL RAISED PANEL DOORS WITH YOUR 1/4" YOUR 1/2" OR 3/4" OR 1/2" ROUTER OR WITH

Professional production quality bit makes it quick and easy to produce matching rails and stiles - the panel raisina bit with ball bearing guide makes the raised panel perfect every time!



RAISED PANEL ROUTER BIT ALL BEARING

CARBIDE TIPPED


\*2" Large Diameter (1/4" Shank)

\*3-1/2" Large Diameter (1/2" Shank) 4-5/8" Large Diameter (Shaper)



\*REVERSIBLE COMBINATION **RAIL and STILE BIT** 

(For making matching rails and stiles in raised pan doors, etc.) Works with stock from 11/16" to 7/8".



ITEM # PRICE/SET SIZE & FORM 1/4" Shank Router #1301 \$69.95 1/2" Shank Router #1302 \$79.95 1/2" Shaper

#1303 \$99.95 Regular Value Over \$150.00!



# CARBIDE TIPPED ROUTER BITS • PROFESSIONAL PRODUCTION QUALITY GUARANTEED • WHEN ORDERING ANY THREE OR MORE DEDUCT \$1.00 EACH . FREE SHIPPING IN CONTIGUOUS USA

| ITEM     | DESCRIPTION (ALL 2 FLUTED)                        | SHANK | PRICE   |                 |
|----------|---|-------|---------|-----------------|
| NO.      | DESCRIPTION (ALL 2 PLOTED)                        | SIZE  |         |                 |
| #1314    | ROUND OVER - 1/8" Radius                          | 1/4"  | \$11.00 |                 |
| #1315    | ROUND OVER - 3/16" Radius                         | 1/4"  | \$11.00 |                 |
| #1368    | ROUND OVER - 1/4" Radius                          | 1/4"  | \$12.00 |                 |
| #1316    | ROUND OVER - 5/16" Radius                         | 1/4"  | \$14.00 |                 |
| #1369    | ROUND OVER - 3/8" Radius                          | 1/4"  | \$15.00 |                 |
| #1370    | ROUND OVER - 1/2" Radius                          | 1/4"  | \$17.00 |                 |
| #1317    | ROUND OVER - 1/4" Radius                          | 1/2"  | \$12.00 |                 |
| #1318    | ROUND OVER - 3/8" Radius                          | 1/2"  | \$15.50 |                 |
| #1319    | ROUND DVER - 1/2" Radius                          | 1/2"  | \$17.00 |                 |
| #1320    | ROUNO OVER - 3/4" Radius                          | 1/2"  | \$21.00 | 1 :11           |
| #1333    | TONGUE & GROOVE - Straight                        | 1/4"  | \$29.00 |                 |
| #1334    | TONGUE & GRDOVE - Straight                        | 1/2"  | \$29.00 |                 |
| #1335    | TONGUE & GROOVE - Wedge                           | 1/4"  | \$29.00 |                 |
| #1336    | TONGUE & GRODVE - Wedge                           | 1/2"  | \$29.00 | P               |
| #1337    | FLUSH TRIM -3/8" Diameter -1"Cutting Length       | 1/4"  | \$ 7.50 |                 |
| #1338    | FLUSH TRIM -1/2" Diameter -1"Cutting Length       | 1/4"  | \$ 8.00 |                 |
| #1339    | FLUSH TRIM -1/2" Diameter -1-3/16" Cutting Length | 1/2"  | \$ 8.00 |                 |
| #1340    | PATTERN / FLUSH TRIM -1/2" Diameter               | 1/4"  | \$15.00 |                 |
| #1341    | PATTERN / FLUSH TRIM -1/2 Diameter                | 1/4"  | \$17.00 |                 |
| #1342    | PATTERN / FLUSH TRIM -3/4" Diameter               | 1/2"  | \$19.00 |                 |
|          |   |       | -       |                 |
| #1351    | LOCKMITRE -7/8" Cutting Length                    | 1/4"  | \$32.00 |                 |
| #1352    | LOCKMITRE -1-1/8" Cutting Length                  | 1/2"  | \$45.00 | 2               |
| #1353    | DGEE RAISED PANEL -2"Large Diameter               | 1/4"  | \$28.00 | l L             |
| #1354    | OGEE RAISED PANEL -2-3/4" Large Diameter          | 1/2"  | \$32.95 |                 |
| #1389    | SPIRAL UPCUT - 1/8" Diameter (solid carbide)      | 1/4"* | \$ 9.95 |                 |
| #1390    | SPIRAL UPCUT - 1/4" Diameter (solid carbide)      | 1/4"  | \$13.25 |                 |
| #1391    | SPIRAL UPCUT - 1/4" Diameter (solid carbide)      | 1/2"* | \$15.45 | *PROPER ADAPTER |
| #1392    | SPIRAL UPCUT - 3/8" Diameter (solid carbide)      | 1/2"* | \$26.45 | WILL BE         |
| #1393    | SPIRAL UPCUT - 1/2" Diameter (solid carbide)      | 1/2"  | \$33.00 | SUPPLIED        |
| <u> </u> |   |       |         |                 |

| ITEM<br>NO. | DESCRIPTION (ALL 2 FLUTED)          | SHANK<br>SIZE | PRICE   |  |
|-------------|-------------------------------------|---------------|---------|--|
|             | MOLDING PLANES                      |               |         | . 🖫 ]                                    |
| #1362       | 1" C.L                              | 1/4"          | \$24.95 |  |
| #1363       | 1-5/8" C.L.                         | 1/2"          | \$29.95 | 7  |
| #1364       | 1-5/8" C.L.                         | 1/2"          | \$31.95 |  |
| #1365       | 1" C.L. #1362 #1364                 | 1/4"          | \$31.95 | #1365                                    |
| #1366       | 1-11/16" C.L. #1363                 | 1/2"          | \$31.95 | #1366                                    |
| #1330       | BULL NOSE - 1/2" Diameter of Circle | 1/4"          | \$16.00 |  |
| #1331       | BULL NDSE - 3/4" Diameter of Circle | 1/4"          | \$21.00 |  |
| #1332       | BULL NOSE - 3/4" Diameter of Circle | 1/2"          | \$21.00 |  |
| #1371       | STRAIGHT - 1/4" Diameter            | 1/4"          | \$ 6.50 |  |
| #1372       | STRAIGHT - 3/8" Diameter            | 1/4"          | \$ 6.50 |  |
| #1373       | STRAIGHT - 1/2" Diameter            | 1/4"          | \$ 7.00 |  |
| #1374       | STRAIGHT - 3/4" Diameter            | 1/4"          | \$ 9.50 | in i |
| #1375       | STRAIGHT - 3/8" Diameter            | 1/2"          | \$ 7.50 | nun i                                    |
| #1376       | STRAIGHT - 1/2" Diameter            | 1/2"          | \$ 8.00 |  |
| #1377       | STRAIGHT - 3/4" Diameter            | 1/2"          | \$10.00 | ***                                      |
| #1378       | COVE - 1/4" Radius                  | 1/4"          | \$12.00 |  |
| #1379       | COVE - 3/8" Radius                  | 1/4"          | \$13.00 |  |
| #1380       | COVE - 1/2" Radius                  | 1/4"          | \$14.00 |  |
| #1381       | COVE - 1/2" Radius                  | 1/2"          | \$15.00 |  |
| #1382       | ROMAN OGEE - 5/32" Radius           | 1/4"          | \$16.00 |  |
| #1383       | RDMAN OGEE - 1/4" Radius            | 1/4"          | \$17.00 |  |
| #1384       | RDMAN OGEE - 1/4" Radius            | 1/2"          | \$18.00 |  |

BISCUIT JOINING SET

5/32" Slot Cutter - 1/4" Shank. Plus 250 #20 Biscuits.

"Biscuit Joining with your Router", Instructional sheet included. Order Item #1385







# TECHNICAL HELP & EXPERT ADVICE • CUSTOMER SERVICE BEFORE & AFTER SALE • FREE 40 PAGE CATALOG

# **CONTROL THE SPEED** OF YOUR ROUTER

ROUT AT THE SPEED THAT GIVES THE BEST RESULTS WITH THE **WOOD & BIT YOU ARE USING!** FFATURES:


- Works with all routers 3-1/4" HP or LESS-120V 15 Amp
- Full horsepower and torque at all speeds
- Gives your router a feature only available on routers costing hundreds of dollars!





Forstner bits are designed to drill flat bottom or through holes cleanly in end grain, thin stock, veneers & regular stock. Comes with it's own attractive wooden hox.

|   | Price    | Price    | 6 |
|---|----------|----------|---|
| 7 PIECE SET-Item #1386<br>/4" TO 1", in 1/8" increments         | \$ 40.65 | \$ 25.95 |   |
| 6 PIECE SET - Item #1387<br>  /4" TO 2-1/8", In 1/8" Increments | 141.20   | 69.95    | 6 |
| 24 PIECE SET-Item #1388   | 298.80   | 189.95   |   |



To Order By MasterCard, VISA or Discover. Call Toll-Free 7 Day - 24 Hour Order Service

Or Send Check to: MLCS, Ltd. P.O. Box 4053 PY, Rydal, PA 19046

# Tricks of the Trade


# Calling All Tricksters!

We know you're out there, working in your shop, hoarding your best secrets from the rest of the woodworking world! Well, fess up! Share the tricks that make your woodworking tasks easier and we'll put your name in print — and pay \_SS, the Editor. you \$35!

# Get a Grip

The handles from discarded plumbing fixtures can often be easily modified for use as knobs on shop jigs and devices. The plastic and metals (usually brass) of which these handles are made can be drilled and tapped to serve as huge "wing nuts," or fitted with stove bolts and nuts for tightening into a T-nut or threaded insert.


Edwin Borgeson Portland, Oregon



# Stretch to Fit

My bench model drill press often gave me problems when the work piece was too tall to fit under the drill or too short to sit on the base and still be reached. I solved this by taking the original post and a piece of 11/3" water pipe to the local vocational education school where they were glad to turn it down making the new one about five inches longer. It really has helped and I've had no reason to put the original back.

James A. Johnson Brunswick, Ohio




### Hooked on Hold-down

I had to replace a badly worn bench hook and made the new one with one end undercut. It gives me a better grip on thin stock and round pieces, such as the dowel rods.

> The board is hardwood, with a base of 5" x 13" x ¾". The ends, 1½" square, are fastened with glue and 1/2" dowels. The undercut is about 3/11 inch deep with a 60° bevel.

Percy W. Blandford Stratford, England



#### **New Angle to Planing Block**

A block with an acute-angled V cut in it is not a new idea for holding thin material on edge over the bench top. It might be screwed to the bench top or made removable with dowel rods in the block going down squarely into holes in the bench top. Even before wear takes place, the block is liable to rise under the pressure of planing. You can cure this by arranging the dowel pegs at a slight angle, so planing pressure has a tightening effect on them.

Make the block and drill for the pegs, then use it as a template or jig for drilling the bench top, before gluing in the dowels.

Will Atkins Chicago, Illinois

# **Run Those Panty Hose** to the Shop

Used panty hose yield several effective shop vac pre-filters. Put the filter into one leg, cut the hose to length, and reinstall the filter. Knot the cut end and you have another pre-filter.

This is especially effective in keeping larger particles from clogging the filter, especially in lower-powered units.

Chuck Kubin Denver, Colorado

# Tricks of the Trade

# **Dust Collection's in The Bag**

Rather than purchase an after market dust collection system for a contractor-type table saw I decided to adopt the following dual strategy.


Box in the sides of the legs with 7-mill plastic sheet fastened with duct tape. The plastic sheets are not taped all the way to the bottom of each leg. Leave four inches untaped giving you loose flaps. Next, make a shallow, four-inch deep tray using thin plywood to fit between the legs and slide it in place. The plastic flaps are then inserted in the tray. This

A Turn-Around that Makes Cents
The life of a sanding sleeve can be extended by reversing it on the drum. Worn and clogged abrasive grains take on a new life with this reversal of rotation.

Thomas LaMance Prewitt, New Mexico

allows the saw dust to fall naturally into the catch tray, which can be slid out easily and emptied when full.

> Eric Worden Halifax, Nova Scotia



# A Boring Problem Solved

Even when drilling simple right angle holes, I never got the accuracy I needed. The holes were always a few degrees off when I used my hand-


held drill. So, I made a couple of basic jigs to help.

I visited a local hobby shop and purchased short lengths of brass tubing in various diameters. Back in the shop I cut about 1" off each size and using epoxy, affixed them to one leg of a 1" x 1" corner bracket, which I checked to make sure was square. In the smaller diameters I mounted 2 tubes per bracket, side by side.

To use, I select a tube just larger than the bit I'm using, hold the bracket against the surface to be drilled, and run the bit down through the tube.

R. B. Himes Vienna, Ohio

Tricks of the Trade shares readers' ideas for making woodworking tasks easier and safer. Send your original, unpublished ideas to Tricks of the Trade, Popular Woodworking, 1507 Dana Ave. Cincinnati, Ohio. If needed, please illustrate with a focused, color photo or diagram. We pay \$35 for each trick we publish.



Triangle sanders, detail sanders, corner sanders—call them what you will. Seems like everybody in the business is introducing their version these days. And frankly, you can pick up one of the newcomers a whole lot cheaper than this one.

The Fein Triangle Sander. The original technology. The one the others want to be. The one you'll want to compare the others with.

(Before you get any ideas about saving a bundle.)

Start comparing the moment you flip the switch. Feel the vibration. Notice the tingle. Check out the numbness that comes standard with some models. Put down each tool as it becomes bothersome. You're left holding the Fein. Hold it as long as you like. No buzz. The Fein is built for heavy-duty, continuous use. Balanced for comfort and precision sanding.

Now put the Fein to the surface. It stays where you put it. Removes what you want. No more, no less. No wandering, no running away, no banging or hammering against adjoining perpendicular surfaces. *Precision*.

Now try to make the others do what you just did with the Fein. All the time asking yourself, "Is this what I really want?" (No choice.)

To learn more about the Fein Triangle Sander and its many accessories (for sanding or sawing or scraping or polishing), call 1-800-441-9878.

Fein Power Tools Inc., 3019 W. Carson St., Pittsburgh, PA 15204.

Celebrating a Century Since Fein Invented the World's First Power Tool.

# Finishing Forum

he Finishing Forum is an ongo-I ing discussion about the art of wood finishing. If you have a question or a problem, we'd like to help. If you have a tip or secret to share, or you recently tried a new product. write: The Finishing Forum, c/o Popular Woodworking, 1507 Dana Ave., Cincinnati, OH 45207. Letters may be edited for clarity.

# In A Pickle About A Finish

I am in the process of making a crib for my daughter-in-law, and she has requested a pickled finish on the project. I have looked through all my back issues to find information on this type of finish, but have not located any information. Would you please give me some ideas on how to go about putting a pickled finish on my project?

> Dave Johnson Johnson City, Tennessee

Putting a pickled finish on your crib shouldn't be too difficult. I'll give you the basic idea and then you can experiment to get the look you want. A pickled finish gives the appearance of a surface that was painted and subsequently stripped, leaving traces of the paint. There's no rule concerning how much of the paint should remain on the wood, it's a matter of personal taste, but the color of the paint is usually white or off-white.

Try thinning white paint with mineral spirits or turpentine until it's about the consistency of whole milk. (You could also try a low-odor alternative such as latex semi-gloss enamel.) Apply this to your wood liberally and let it soak in for twenty minutes or so. Wipe off the surplus until the amount of paint remaining on the wood pleases you. If too much remains, let the paint dry overnight and then scrub the surface down with fine steel wool and thinner, leaving paint in the intricacies and corners. Wipe off all surplus. For a more authentic look, let the paint dry a week or so and strip the surplus off with remover.

Finish up by wiping all residue with denatured alcohol so that subsequent coatings will bond properly. (Many removers contain retarders such as paraffin.) Remember that the type of wood you use will determine how much paint gets absorbed. Pine will soak up a lot more pigment than maple.

You can "layer" slightly different colors on the wood and then strip off the surplus. creating a very convincing-looking imitation of an old piece that has been painted and then partially stripped. I recently finished a hand carved mirror frame in pine this way and was very pleased with the results. I used wax as a topcoat and liked the informal look it gave, though you'll want a more substantial film or overcoat, such as varnish, on your crib. (I'd suggest a water base polyurethane varnish.)

Remember that someone else's definition of pickling may vary from mine and the formula they give for producing it could be quite different. But you have the basic idea: a surface that looks as if it was painted long ago and then stripped at a later date, something like old English pan-

# WE MAKE ABRASIVE BELTS ANY SIZE, ANY GRIT!

# Garnet & Aluminum Oxide Cabinet paper

50/pk 100/pk 60D \$16.70 \$30.00C 27 80C 80D 15.60 100 thru 150C 14.50 25.60C

Garnet & Aluminum Oxide

Finishing paper 80A \$11.15 \$18.90C 100 thru 280A 10.00 16 70C Silicon Carbide No-Load

Finishing paper 100 thru 400A \$12.25 \$21.25C 9×11 SHEETS - "C" = 100

#### Abrasive Belts

A/O RESIN CLOTH, ANY GRIT 1×30 \$.81 ea 3 × 24 \$.93 ea 1 × 42 .81 ea  $3 \times 27$ .96 ea  $1 \times 44$ .81 ea 4 × 213/4 1.06 ea 2½×16 .85 ea 4 × 24 1.10 ea  $3 \times 18$ .86 ea 4 × 36 1.35 ea  $3 \times 21$ .90 ea 6 x 48 3.50 ea .93 ea 21/4 × 80  $3 \times 23\%$ 3.25 ea OTHER SIZES ON REQUEST

★We stock a full line of adhesive and velcro type discs for all your power tool needs.

# 9. mouneing...


# PORTER+CABLE

MODEL Price 330 Speed Bloc Finish Sander \$65.00 332 Quicksand 5" Random Orbital w/PSA Pad 70.00 352vs 3 X 21 vs Belt Sander w/Dust Bag 179.50 Quicksand w/HOOK & LOOP, Dustless 79.50 334 Quicksand w/STIKIT, Dustless

79.50 505 1/2 Sheet Finish Sander 132.00 194.00 9853s Cordless Drill Kit W/2 Batt and case

\*MasterCard, VISA, C.O.D. or Check \*SATISFACTION GUARANTEED!!!

\*CALL FOR FREE CATALOG \*TX & NV add appropriate sales tax



P. O. Box B865021 Plano, TX 75086 (214)377-9779

# WoodMatch CD-RO

# Discover the perfect woods for your work!

Criteria Search == 

WoodMatch is available for PC and Mac computers, in CD-ROM or floppy versions!

Woods of the World Pre, our corporate and institutional version covering 950 species, is available for \$249.

We also sell CD-ROM drives and software bundles.

WoodMatch is a powerful, user-friendly, multimedia resource tool providing detailed information on hundreds of wood species. WoodMatch is designed for architects, woodworking firms, schools and wood researchers. Features include:

 Data on more than 300 tropical and temperate species, including all the world's commonly-traded. and many lesser-known, species. Plus, information on 50 wood-based composite products

Aesthetic, mechanical, physical and woodworking properties-up to 85 categories of information on each species! Thousands of common names Environmental status of hundreds of woods. Fullcolor, high-resolution pictures of every wood and composite product. Color maps showing the location

 Search for woods fitting any combination of color, common use, environmental status, weight, hardness, and more!

Instantly compare five common properties of any one species to any other nine species you choose or compare the appearance of nine different woods

- A real database. Store your own information on woodworking properties, sources, etc.
- All numerical data in metric and English. A truly international product.
- Extensive wood glossary, more than 60 minutes of video, on-line tutorial, data on certified "sustainable" wood sources and environmentally-sensitive wood oroducts, and more!

# 30-day money back guarantee!

Tree Talk, Inc. P.B. Box 428, 431 Pine St. Barlington, VT 85482 USA PHONE 802-863-6789

FAX 802-863-4344

"The most important computer resource on wood you can ewa..." Workbench Magazine

"A fabulous concept..." John Amo, Fine Woodworking Magazine "We tried it, we liked it ... " Popular Woodworking Magazine

"A real winner, a great deal of extremely useful information about weed..." G. Berlyn, Yale University, J. Sustainable Forestry

# by Tom Wisshack

eling in pine with traces of white lead paint or whitewash. How much or how little paint you allow it to remain in the wood is a matter of personal taste. The real secret lies in your willingness to experiment and be open to whatever tools, materials and techniques help you achieve the look you're want. If you adopt this attitude, the results may pleasantly surprise you.

# Fill-er Up?

- I recently built a hall table out of Honduras Rosewood and have some questions about the finishing process. We used Sherwin Williams Sherwood catalytic water white conversion varnish.
- 1. Should I have used a filler for the grain pores, and if so, what type? After the third coat of sprayed-on finish it still has the wood pores visible and open to the touch.
- 2. Should stain be applied before finishing? If so what kind of stain? My rosewood was finished without any stain and has some of the orange streaks through it, which seems to be common in rosewood. All rosewood furniture I have seen is always very dark which, obviously, makes me think it is always stained.

Richard Ruehle Findlay, Ohio

You ask whether or not you should have used a filler on your Honduras Rosewood. Without seeing the piece of furniture, and knowing the kind of use it will be subjected to, I can only tell you how I would finish it. First, I'd use an oil finish or a wiping varnish, such as Formby's Tung Oil Finish. I'd build it up in several coats and then rub it to a satin sheen with mineral oil and steel wool. I'd also consider using wax as a finish.

My personal feeling is that tropical woods, which are sometimes oily by nature anyway, look best with an oil finish. It's partly an aesthetic choice, and partly that oil finishes tend to penetrate more than film finishes like lacquer and varnish. This gives you a better bond. Applying a heavy film finish to Honduras Rosewood carries with it a certain risk because the finish could peel off if not applied carefully. In a nutshell, I find oil finishes more compatible with woods that are oily in nature. It's more common sense than anything else.

This brings me to your question about filling the pores of the wood. I'm against it because I consider this a natural part of wood's tactile quality. The pores in Honduras Rosewood are larger than in other woods. If this is objectionable to you, I would suggest using a wood that is more to your liking from the beginning, rather than modifying it to make it look the way you want. Rosewood is a beautiful wood. Why should we impose ourselves on it in an attempt to make it look like something else? What we end up with is often more like plastic than wood.

As to staining, I would view stain as a tool for evening out the tone that is bound to have some variation on a large piece of furniture. I'd use an aniline dye, dissolved in water, which has the most transparent tone of any stain. I would mimic the colors already present in the wood rather than totally changing its character. The dark color you have learned to associate with Rosewood furniture may be a result of an entirely different kind of Rosewood having been used in manufacturing. Brazilian Rosewood, which was used more in former times, is darker and richer than most Honduras Rosewood. As supplies of Brazilian Rosewood dwindle and the wood becomes scarce (and endangered), other varieties have begun to replace it. Unfortunately, none of them have the richness, the color or the metallic sheen present in this superior wood.


You've asked some very good questions, ones that come up pretty frequently in my work as a woodfinishing consultant. I'm risking appearing like a snob in the advice I'm giving you, but I'm willing to do so in hopes that you can see a deeper meaning in between the lines of my answer. Yes, I'm a purist when it comes to wood and woodfinishing. At the very least I hope you'll benefit from my honesty. Good luck.

**Tom Wisshack** is a woodfinishing consultant and makes and restores fine furniture in Galesburg, Illinois.



# The Little Business That Could

Creative artistry and a skilled hand take scrap wood all the way to the bank.



Ibecame an artist at the age of ten. Since then, I've taught myself to use many mediums, including pen and ink, oils, watercolor and colored pencil. My exploration of wood as an artistic medium eventually led me to a revelation: wood is a more appealing and diverse medium, and unequaled for sensual, visual and tactile pleasure. It echoes with a journey of earthly existence and spiritual evolution.

In the 1980s, Florida underwent tremendous growth. Building materials, wood and scrap lumber showed up on curbs and at roadsides everywhere. I sal-

"I've been paid a minimum of \$200 for a simple wheel barrow piece and up to \$12,000 for a commissioned steam engine with water tower."

vaged and stored until my yard overflowed. From this surplus, I built a 12' x 8' workshop, and at that point, had no other aspirations for the wood I had saved from the landfill. I completed a few basic woodworking projects, but the artist in me began to realize that more was possible with the wood I'd collected. One day, I envisioned something different, and I created a mailbox resembling an old-fashioned mail truck. The spark ignited.


Soon my shop filled with toy boats, trains, planes, bicycles and wagons. Those great piles of discarded objects and scrap wood transformed into three-dimensional sculptural collages.

I think of my work as a manipulation of relationships, between natural and manmade, offering a unification of elemental parts. My earlier works, primitive and bulky, were composed of pine, cedar, birch, popular and bamboo.

# Fire Engine

The body and fenders are cedar, with the running boards and floor boards made of mahogany. The tires are made from pine with poplar rims and spokes. The dashboard sports detailed instrumentation including the ignition and starter switches. Movable pieces include wheels, side mounted searchlight, rear spotlights, steering wheel, gearshift, suction pump handle, hose reel with rubber hose and metal nozzle. Also, the ladder, with grappling hooks, slides in and out by means of a rope on a pulley.

Dimensions: 10"H x 10"W x 24"L









# **Chuck Wagon**

The wagon is made primarily of cedar and pine, with a variety of woods used for other pieces. The hitching runner disconnects and stores beneath the wagon. Movable pieces include the wagon wheels, swiveling steering column and the rear cabinet which opens, closes and locks. Details include a water barrel, medicine cabinet, lanterns, canteens, rope, rifle, and dinner chime outside of the wagon. Inside, a clothing trunk, bedrolls and staples are packed away neatly. The campfire scene includes frying pans, coffeepot, ladles, pots, pans, knives, meat grinder and dishes.

Dimensions: 12"H Base: 16 W x 12"L





For the first five years, I didn't really tell anyone about the kind of work I was doing with wood. My toys, lingering on the shelves of my shop, were given away to family and friends or exchanged for needed supplies, tools and materials. I attended my first wood show in 1985, won awards for my carving and had an epiphany-what I thought was a creative hobby was quickly becoming more than that. My "toys" were becoming works of art.

Eventually, people who liked my work bought enough pieces to provide both the funds and needed encouragement for continuation on this path. So, the eventual transition from hobby into a full-time creative enterprise in 1990 was a natural one.

Co-workers purchased pieces for gifts or personal collections. Art festivals brought income from cash awards and sales, and provided the opportunity to promote my work and to maintain customers. Local exhibitions of my work led to further contact with potential clients and commissions.

Working exclusively as an artist for the past eight years, I focus on designing and creating original, high-quality, wood

sculptures. These are usually in limited number, smaller and more simplified versions than my original pieces, and in series of six to twelve pieces, or groups with a chosen theme. My designs are one-of-akind; I never duplicate any projects.

Pricing for my sculptures takes into consideration complexity and intricacy of the design, materials used and time requirements. I have been paid a minimum of \$200 for a simple wheel barrow piece and up to \$12,000 for a commissioned steam engine with water tower.

While making uncomissioned pieces, I don't really worry about whether or not



dence over technical correctness;

precision is merely a tool of interpretation. Improvisation forms the cornerstone of my approach.

To a great extent, the inspiration for my work is drawn

from childhood memories and travels to foreign lands. Living in Europe, especially Germany and Japan, allowed me the opportunity to experience rich and diverse cultural heritages. Raised in the Great Smoky Mountains, I developed an appreciation for a simple lifestyle and a value system that are harmonious with nature. Traditional woodworking, carving, whittling and a full array of native arts and crafts stimulated my mind to explore new possibilities.

The materials and techniques used to create my work are experimental, eclectic and represent an attempt to maximize the natural beauty of wood. Limited resources or availability of materials can add excitement and a certain freedom to the creative process. My distinctive style of craftsmanship is a synthesis of previous artistic methods and an effort to teach myself woodworking fundamentals.

Through trial-and-error, observation and practice, I continue to learn and apply this knowledge.

The metal and glass items, which I refer to as "tiny-shiny" pieces, are culled from radios, clocks and the like, and kept in a jar waiting for the right application.

I use familiar bench model machines in my work. A band saw, drill press, scroll saw, and disc/belt sander. My basic hand tools consist of clamps, small files, tweezers, razor knives, wire cutters, coping saw, and a large pair of nail clippers. Although it can be time-consuming and difficult, using hand tools gives me the greatest satisfaction.

I don't use blueprints or preliminary drawings because, for me, they inhibit the essence of the piece by imposing restrictions of direction and dimension. I scale dimensions by eye. Each project begins with a feeling, then an idea just appears.

Once the idea exists, form, proportion and choice of materials become major considerations. The selection of wood will be influenced by specific variations of color, graining, contrast, texture and the final effect of finishing.

continued on page 14

# Steam Engine

quieter times.

The boiler and cab are made from oak, with other detail pieces made from walnut, mahogany, cedar, plne, blrch, poplar and bamboo. Movable parts include the 4" drivers and driving arms, the front four wheels, and the break and throttle levers in the cab turn. The trap door on the cab opens and closes. Other features include a completely detailed cab with brake lines held in place by a hook and chain. The track itself is held in place with brass spikes.

Dimensions: 10"H x 7"W x 30"L

the projects will sell-someone always

My current work, delicate and more

sophisticated, makes use of domestic

hardwoods, oak, mahogany, maple, walnut, ash, cherry, as well as metals and

other components. I'm happy to say that 85% of my materials are still "scrap."

The intricate detail I put in my projects

comes from patience, persistence and

discipline. I work toward a sincerity of

expression, which invites participation and contemplation from the viewer. I

hope to uplift the soul with reflections of

my designs are inspired by technical

research, and sometimes they grow from

my imagination. Regardless, personal

expression and perspective take prece-


My philosophy is simple. I follow my own vision and inner voice. Sometimes

seems to like my creations.









# Popular Woodworking Back Issues Fogular Woodwo

Back Issues only \$4.50 and \$3.50 postpaid.

Carve a loon; library steps; a chest for silver flatware;

Hovember '84

# All 1993 and 1994 issues just \$4.50

Tea bag tote; mighty might

|               | carving sailor sam; using the tormek grinder.  |                         | excavator  | r; chess cabinet;                          | Popular Woodworking  |
|---------------|--|-------------------------|------------|--|--|
| September '84 | Hope chest; deck furniture; jewelry box; cantilevered  |                         |            | axe cover;                                 | Sager Products I TOOLI WOLKING   |
|               | rocking horse; bit storage cabinet; revolving bookcase;  |                         |            | basket; rocking<br>ndy stool; 6-foot       | Total Add  |
| L 184         | dual biscuit joinery.  |                         | ladder.    | ildy \$1001, 0-1001                        | HE PROPERTY AND ADDRESS OF THE PARTY AND ADDRE |
| July '54      | Display trays; the art of pipe making; coffee table; three small boats; vanity stool; cartridge box; chip carving.   | September '03           |            | lesk; nesting                              |  |
| May '94       | Turned spice canister; cedar blanket chest; tambour wall   |                         |            | and saw circle                             |  |
| may er        | desk; woodworker's V-block; contemporary desk; nail  |                         |            | g; wind harp;                              | A  |
|               | storage cabinet; nautical flower box.  |                         | child's ro | cker; BB target;                           |  |
| March '84     | Sewing and knitting box; planer stand; carving in the blue   |                         | marqueti   | y; carving.                                | The second   |
|               | whale; walking canes; table saw power feed; walnut quilt   | Jely '83                | Loft a du  | ck; a simple                               |  |
|               | rack.  |                         |            | making pine                                |  |
| January '84   | Doll cradle; carving King Lear; child's sleigh; lathe  |                         |            | es; colonial                               | 1.1.6.4  |
|               | ornaments; beehive octagonal clocks; crayon battleshop.  |                         |            | chief table; puzzle c<br>e; making bow saw |  |
|               |  |                         |            | c, making bow saw                          | s, toddici's toybox.   |
|               | All other issu   | ies just \$3.50         | )          |  |  |
| Saptember '82 | Carved nut bowl and cracker; knock down couch; oak   | November '88            | Panel do   | ors; silver chest; cor                     | rner pewter hutch; country   |
|               | burl jewelry box; shop caddy; peter putter; old mill   |                         | sconce; N  | Massachusetts lowbo                        | oy.  |
|               | wheel; roll top desk II; desktop dolphin.  | September '88           |            |  | ch settee; marionette  |
| May '82       | Lumber storage rack; spiral turning; belt buckles; carved  |                         | bandsaw    | n basket; making cl                        | hisels & gouges; chisel box.   |
|               | corner cabinet; outdoor furniture; jointer push blocks;  | January '88             |            |  | ntwood boxes; heather's desk;  |
|               | wooden jack plane; glass wall sconce.  |                         |            |  | d dice; build a box of   |
| Notember 'St  | Nativity wreath; book caddy; tabletop hockey; disc   | W                       |            | s; box joints on the                       |  |
|               | sander/grinder; Victorian wall box; smoky mountain coon<br>dog; home computer desk; old time toboggan; wooden        | November '87            |            |  | ef carving; wooden buttons;  |
|               | whistles; sandpaper press; sunburst plates.  | Cantamban (81           |            | d chairs; handscrev                        | •  |
| July 'Si      | Chippendale mirror; biscuit-joined table; gardening stool;   | September '87           |            | , , .                                      | lovetails; joiner's toolbox;<br>er Valley desk; utility bench.   |
|               | laminated picture frames; miter jig; Swiss-style chip  | July '87                | _          |  | enov; bed; crotch wood table   |
|               | carving; trastero; turn a teacup.  | any er                  |            | -  | n Arabian stallion part II.  |
| March 'Si     | Dust bench; benchdrop clamp; sailor's work; compact  | May '87                 |            |  | g an Arabian stallion part I;  |
|               | disk storage; spiral lamp bases; dinasour bank; kitchen  |                         |            |  | ngs; home shop wiring.   |
|               | storage rack; occasional table; turned and carved bowl.  | March '87               | _          |  | ork table; ladder-back rocker;   |
| September '86 | Roadrunner whirligig; log turning; serving cart; country   |                         |            | folding stool; makii                       |  |
|               | mailbox; piano music box; toy carousel; cube and canister  | Janu <del>ary</del> '87 | Universa   | l table saw; veneere                       | d vertical tambours;   |
| lala '88      | drum sanding system.   |                         | backgam    | mon board.                                 | •  |
| any as        | Victorian mailbox post; plate shelf; bee hive jewelry box; sliding miter table; writing desk; bentwood Indian boxes. | November '86            |            |  | l; home entertainment;   |
| Hay '90       | Captain's bed; centering tools; child's toybox/chair;  |                         |            | ing wooden signs.                          |  |
| ,             | computer security cabinet; cutlery box; candlestick.   | September '86           |            |  | mirrors; power carver's tool   |
| January '80   | Coffee table; Folding candelabra; ladle; firewood box;   |                         |            | building a wine raci<br>i wall shelf.      | k; marquetry techniques; early   |
|               | butterfly figures; cedar-lined chest; extension cord reel;   | July '88                |            |  | ultimata natia ahair: aaccatta   |
|               | pole lamp.   | early so                |            | rving the human he                         | ultimate patio chair; cassette<br>ad part IV   |
|               |  |                         |            |  |  |
| l<br>I        | Popular Woodworking I  | Back Issues O           | rder form  | ì  | }  |
| Check c       | off the issues you want, cut off this order form, and  |                         |            |  | er made payable to:  |
| Donular       | Woodworking <sup>®</sup>   |                         |            |  | į  |
| Populai       | MOOUMOLINING   | All \$4.5               | e issues   | A  | II \$3.50 issues   |
| Back Issues   | •  | □ Nov '9                | 94 (58104) | ☐ Sep '92 (59                              | 1968) 🗌 Jan '88 (59940)  |
| 1507 Dana     |  | ☐ Sep '9·               | 4 (58094)  | ☐ May '92 (5                               | 9966) 🛘 Nov '87 (59939)  |
|               | Ohio 45207   | ☐ Jul '94               | (58074)    | □ Nov '91 (59                              | 9963) 🛘 Sep '87 (59938)  |
| Name          |  | ☐ May '9                | 94 (58054) | ☐ Jul '91 (599                             | •  |
|               |  | ☐ Mar '9                |            | -  | 9959)  |
|               |  | ☐ Jan '94               |            |  | 956)   |
|               | Zip  | ☐ Nov '9                |            | ☐ Jul '90 (599                             |  |
|               | 1  | ☐ Sep '93               |            | -  | 9954)  |
|               | lease add \$1 per issue in U.S. funds only.<br>ks for delivery. Ohio residents enclose 5.5%                          | ☐ Jul '93               |            | ☐ Jan '90 (59                              |  |
|               | s include shipping & handling.   | jui 93                  | (37713)    |  | 992)   |
|               | Total Enclosed \$  |                         |            | ☐ Sep '88 (59                              | •  |
|               |  |                         |            |  | 1944) pwad j   |



continued from page 12

To preserve the sculptural element, machines are only used for rough cuts. By starting with wheels, the ultimate size of the piece and its overall definition and character are determined.

My preferences for assembling include a common yellow carpenter's glue for wood and a super adhesive glue for metal, fabric, artifacts, or Plexiglas. Before attaching metal parts, I rub the contact side over a piece of medium grit sandpaper, which will make it porous for better adherence. Polishing the surface with jeweler's cream adds shine and protection.

Surface images are enhanced by hand sanding and shaping. Leaving subtle imperfections such as tiny scratches, knots and dings, gives personality plus

an antique appearance. Selective detailing adds warmth, softens lines and enlivens the material.

The final statement, finishing, gives animation and highlights colors for a free-flowing visual harmony. I use a high gloss tung oil applied in a dust-

free area, because it dries fast, and doesn't leave bubbles in the finish. The first coat absorbs quickly and the second coat can be applied in about an hour, but allowing 12 to 24 hours for proper drying is best. Before adding a third coat, steel wool is used to remove any rough surfaces, thus allowing it to develop a deep, rich luster. After a full day's drying time, the steel wool/tung oil process can be repeated for each additional coat, depending upon the desired effect of the gloss. For my smaller pieces, two coats are applied, and six for the larger ones.

Brushes clean easily with warm water and dish detergent.

Each design varies in degree of detail and movable features, which may include wheels, windows, visors, lights, doors, steering wheels, pedals, gearshifts, swivel seats, radiator caps, hoses and ladders.

I hesitate to quantify my work in terms of time, or total number of parts used, since it's subject to many other variables. However, the average can take from two to seven months for completion.

My craft is a continuous process of learning. It rewards me with many new experiences, and offers a view to a future creation on the horizon. I think I'm lucky to have found something I love to do that I do well.

And, it takes strength—strength to find patience and dedication inside yourself, and strength to break the rules, if necessary, to make your living. PW

Joseph Ramsey, originally from North Carolina, now resides in a rustic 1880s home in Ormond Beach, Florida. He makes his living by creating one-of-a-kind "toys."

# Make Your Own Lumber! WITH A WOOD-MIZER PORTABLE SAWMILL Sawing your own lumber lowers costs and improves quality without trailer from All-products mill, kiln, \$6995! and edger catalog\*: \$2.00; 60-minute video: \$10.00. 13,000

# SAVE ALL OF YOUR ISSUES OF Popular Woodworking

Use this handsome binder to organize Popular Woodworking for use as a valuable shop reference. The vinyl cover and durable construction will protect your personal Popular Woodworking collection for years to come. Order today for just \$11.95, postpaid. (Ohio residents add 5.5%

sales tax. Outside U.S. enclose \$13.95 in U.S. funds.)

Send check or money order to: Popular Woodworking, Binder Editor, 1507 Dana Avenue Cincinnati, Ohio 45207

# Get a grip!

with THE GRIPPER..

The amazing tool that turns faucet handles easily.

- Lightweight
- Won't slip
- Can't scratch chrome fixtures and finishes
- Universal fit – guaranteed!
- No assembly - ready to use
- Won't rust or crack
- Turns stubborn and hard-to-reach handles with ease!

# **ORDER NOW**

Send \$6.95 plus \$1.50 postage & handling to:

Al-Len Pattern Company 1931 Perry Hwy. Dept. PW Fredonia, PA 16124 (412)475-3708

# **RETAILERS: PUT** POPULAR WOODWORKING TO WORK FOR YOU!

Carry Popular Woodworking in

your store, and your profits are sure to soar! And now, there are two can't-lose programs to choose

from:

each



# **Maximum Profits:**

■ 50% discount Non-Returnable Program

#### **Guaranteed Sales:**

■ 40% discount Returnable Program

For more information about the NO-RISK DEALER PROGRAM, call Vicki Keaton at 513/531-2690, ext. 327.

# Fire Rescue



The body is made of poplar, while the tires are made of cedar and poplar. Movable parts include the gearshift, steering wheel, swiveling spotlights. The bucket seats swivel, the rear doors open, close and lock, and the sliding side doors operate. Other details include the siren, which is placed prominently on the front bumper, an exterior and interior fire extinguisher, and full instrumentation on the dash and in the rear area. The gurney is removable—and it rolls.

Dimensions: 10"H x 8"W x 18"L









# Hollows & Rounds

Learn more about collecting and using these valuable tools — they're more beneficial to your woodshop than you might think!


part from the wooden rabbet plane, hollows and rounds are perhaps the simplest looking of all wooden planes. The relatively narrow, 9" slab of beech, usually aged to a dark, dull brown, has no fancy profile like other moulding planes, no large wedge or imposing iron, and no fancy boxing or abundance of chamfers adorning the stock. But this apparent simplicity hides a surprising amount of sophistication. If you've never used one of these planes before you might be very surprised at how much they can add to your woodworking.

Many hollows and rounds can be found today in antique stores, yard sales and flea markets — an indication of the important role they once played in woodworkers' crafting. It could be difficult for someone unfamiliar with them to guess how they are used. There are no fences, shoulders, or depth stops — just a simple curved sole that can appear very difficult to use. Where do you start with such a plane? What do you guide it against, and how can you control how deeply it works?

# Naming and Sizing Conventions

Unlike most moulding planes, which are named for the shapes they cut, hollows and rounds are named for their own profiles, which are the opposite of the shapes they produce. Thus the plane with a convex sole is called a round plane even though it cuts a hollow, and the plane with a concave sole, the hollow, actually cuts a convex shape, a round (figure 1).

Although at first glance one hollow or round looks much like another (except for the fact that it might be bigger or smaller) there are, in fact, different kinds of hollows and rounds. The most common has square-set irons (blades) bed-



Don't confuse the size, which is usually indicated by a stamp on the heel of the plane, with the shape of the arc. For example, a plane with %" stamped on its heel indicates how many eighths of an inch wide the profile the plane will cut. You could assume that profile will be ½" wide, but this gives no indication of how tight or flat the profile of its cutting edge may be. Manufacturers frequently indicated the size of the arc by noting the relative measurements in their catalogs. Some simply included a diagram duplicating the exact profile, and others printed tables of the sizes of the circles worked by various models. Measurements varied considerably from one manufacturer to another. In fact, after one of the biggest manufacturers of moulding planes, The Ohio Tool

Company, absorbed another plane man-

ferent shapes of hollows and rounds,

that is, different arcs. Those that cut an

arc one-sixth of a circle (60° of arc) are

most common, but both flatter and

tighter arcs also exist.


ufacturer, it had to publish two sets of arc measurements: one for its own planes, and one for the absorbed company.

### **Specialized Varieties**

Planes that cut 90° arcs are called Table hollows and rounds, and are used primarily for cutting the two halves of a rule joint (to join drop leaves to table tops). But either of these planes can be very useful used in conjunction with regular hollows and rounds. Apart from the tighter arc, a table hollow differs from a regular hollow by being beveled on both sides of the stock instead of just one. More expensive models were also made with fences, something unknown with regular hollows and rounds. However, models with a fence are often mistaken for moulding planes.

Another major variety is the side round. This type may have a profile consisting of a quarter round or a half round, (figure 2). It was made in handed pairs left and right — but note that there is no side hollow plane.

Apart from regular hollows and rounds




there are several other old wooden planes that cut similar shapes. This group includes planes that have stocks similar to those of bench planes rather than the slim moulding plane type, and often have double irons (cutting irons and capirons). Ship hollows and ship rounds, gutter planes, forkstaffs, and nosing planes are the most prominent of this group.

#### **Pairs and Sets**

Hollows and rounds were originally sold in sets of pairs. It's still possible to turn up a matched pair, often in a custommade box containing several such pairs. But don't think that a single plane is useless without its mate or the rest of its set. It's up to you to decide how many you would like. Cabinetmakers and joiners who worked in shops kept many more sizes and types than a carpenter would have carried around. Even manufacturers could not agree how many planes


constituted a "set."

As mentioned earlier, apart from the fractional number indicating width stamped on a plane's heel, most planes bear another number: the manufacturer's code for a particular size. Since there was no uniform system among manufacturers, you cannot assume that by collecting a mixed group of planes numbered consecutively one through 15, for example, you will have all available sizes in this range. In America, makers often numbered their hollows and rounds from 2 to 30, using even numbers only and starting with planes 1/4" wide, increasing by increments of a quarter of an inch up to 2". In Britain, on the other hand, a common system was to use both odd and even numbers and to sell sets of eighteen pairs ranging from 1/4" wide to 1½" wide, increasing in increments of sixteenths of an inch. In addition, using both odd and even numbers Figure 2
A pair of side rounds, seen from the front



made it possible to sell groups of socalled "half sets" of nine pairs consisting of only odd or even numbers.

Yet a third number sometimes appears on the heel of these planes. This is the manufacturer's model or catalog number. It simply indicates the plane's generic type, that is, a hollow or round plane, as opposed to any other sort of plane. With so many sizes and graduations it's possible to find planes of almost any size from 1/6" wide on up, and in various arcs, making a definitive 'set' far greater than the nominal nine or eighteen. You could collect hollows and rounds for years and still find new types. Although these numbers can be very valuable to the collector, as a woodworker, you're probably better off ignoring all of them. The best plan is to simply acquire whatever planes cross your path until a



growing collection and a little experience make more choices meaningful.

# **Preparation for Use**

Hollows and rounds are a little more difficult to use than other planes because they have no built-in fence or depth stop. This often masks the fact that difficulty in using them may be due not to inexperience, but to the plane being poorly set up. First of all, the iron must be sharp and correctly set. After sharpening, the flat side of the iron must be truly flat with no pitting or scratches —




Figure 4
Profile of cutting edges of A. Round plane iron B. Skewed round plane iron C. Side round plane iron

at least in the vicinity of the edge and the bevel must be regular across the entire profile. The angle of the bevel will vary according to the set of the iron in the stock and the hardness of the wood being worked. Experience will ultimately dictate a bevel somewhere between 20° and 30°, so start off by forming a bevel around 24°. If the edge breaks down too quickly, increase the angle of the bevel. If it doesn't break down, you can aim for less angle. But bear in mind that no matter how fine an edge you put on the iron, the profile of the edge must match the profile of the sole.

Matching the cutting edge of the iron to the profile of the sole is likely to be your first job when reconditioning an old plane. Not only is the sole likely to have been worn out of shape but inept sharpening is likely to have further increased the disparity. Only in extreme cases resulting from excessive wear or abuse should you attempt to match the sole to the iron. Rather, the iron should be matched to the sole. If the discrepancy is gross, put the iron in the stock, secure it lightly with the wedge, and tap it gently until the entire width of the iron can be seen protruding through the sole as you sight along it (figure 3). Mark the iron with a fine felt-tipped pen held flat against the sole and grind to this line, establishing the correct bevel as you do so. Since many planes are very old, the stock may have shrunk in width. This will require further careful grinding so that the iron does not protrude from the sides.

Note that the irons of skewed planes, and to a much greater extent the irons of side rounds, do not display a symmetrical arc. Extra care is needed when stoning these irons to maintain the correct profiles, as shown in *figure 4*.

As is common with practically all moulding planes, most hollows and rounds you find will have laminated irons. The softer metal used for the back of the cutting edge and the thin shank that extends up through the plane's throat tend to rust easily, even though the actual cutting edge may be in good condition. Clean this part well, but treat the malleable metal gently, so that flaking rust or pitted surfaces do not interfere with the removal and adjustment of the iron. Even if the throat is clean, and the iron well-bedded, correctly shaped, and well sharpened, a damaged or poorly shaped wedge can cause endless frustration. The sharp end of the wedge should be beveled in order to direct the shavings out of the stock. Over time the wedge may become blunted and act as an obstruction. This causes the shavings to jam up and choke the throat in a hardto-remove accordion-like mass. Resist the temptation to remove this mass with a knife or awl, you might further damage

the smoothness of the mouth and throat. Remove the wedge and refit it correctly so that it sits without rocking against the bed of the throat and is correctly tapered and beveled down to its tip.





Figure 5
Showing spring line on moulding plane indicating angle at which to hold plane, and round planes always hold perpendicular to work



# Operation

Hollows and rounds are sometimes represented as the black sheep of the moulding plane family since they cut no distinct, specific shape, such as an ogee, a cavetto, an astragal or a bead. They're said to be used only in place of a specific plane in a makeshift effort to reproduce a required moulding. In short, they cut no moulding that is properly their own.

While pinch-hitting for a missing moulding plane is indeed one of their strengths, it's by no means their sole purpose. They're also invaluable for completing and trimming moldings begun by other planes (not to mention moldings formed with the router or by using the shaper). They are also important for sculptural shaping, and of course, working hollow and round shapes in their own rightsuch as linenfold paneling. Furthermore, when you consider their potential use as substitutes for many router, shaper, and other power tools it becomes harder to devalue these especially useful tools.

The main problem you're liable to run into when using these planes for the first time concerns the angle at which the plane should be held to the work. Most moulding planes are designed with spring. This is usually indicated by a line inscribed on the toe of the tool showing the vertical angle at which the plane must be held to the work. There is no spring line on a hollow or round plane, and since the cutting profile should represent a regular section of a circle, perhaps you might think it would make no difference how the plane was held. In fact it makes all the difference, although initially the plane is usually held perpendicular to the work (figure 5).

The second problem has to do with



# **Preview Woodwor**

Just one year of Woodworker gives you dozens of handsome projects that vou can build in a weekend or two.

Instructions are clear. Step-by-step photos show critical steps. Detailed drawings and complete cutting lists make understanding the projects easy so you can get right to work.

But there's more than just great projects in Woodworker. You'll find articles on new techniques and time-saving secrets to help you work smarter, not harder, in your shop. The idea file will surely spark your imagination while tool reviews will keep you up with the latest equipment.

See for yourself when you mail the coupon below to receive a FREE examination issue.

| (B)((E)(NA), VA  | -   | -  | -  |   |
|--|---|--|--|---|
| Minged Coffee Table Plants a spirit webful/regly inthe with new strongs spirit topics. A fundate   |   |  | to the same of the same of   |   |
| Signature investment and security of the secur |   | 1-4  | Employer, order statement of the control of the con | Section (no   |
| and the part of 1 of 1 of the con- good for the control of the con | oppositioner and a dallitty stitled<br>spirit to i traus up tall make and<br>gravier desse the same and<br>gravier desse the same and<br>the stitutes plant oriely over the   | EMBO STORY S | Management of the control of the con | The district of the second of |
| us fryede i ye mai'r rigi<br>yerning yldar yn yn rei<br>yd har glawn Ym de'r<br>yl y mai'r dei yn yldar<br>yn y yn y yn y yn y yn y yn y y yn y y<br>yn y y y y  | remy artists they demonstrate the second of the beauty artists of |  | Control of the contro | Andrew grandway and expension of any and any and any and any and any any and any any and any  |
| age a test data or refere or series sales day the series factor of separated factors and the series of series and separated factors are determined to date of one or a few of securities of the series date of parameters of the series date of the  |   | Continue of the spine of   | a-management   |   |

| Woodworker | FREE | ISSUE | <b>OFFER</b> |
|------------|------|-------|--------------|
|            |      |       |              |

YES! Rush my FREE preview issue of Woodworker. If I don't enjoy the tips, techniques and projects, I'll return your invoice marked "cancel" and owe nothing. Or I'll honor it and pay just \$14.97 for 5 more issues (a total of 6 big issues in all). I save 16% off the newsstand rate.

Zip

Name

Address

City

Outside U.S. add \$7 (includes GST in Canada); remit in U.S. funds.


Newsstand rate: \$17.94. Watch for your first issue in about 5 weeks!

M0895PW



PO BOX 5383 HARLAN, IA 51593-0883

Figure 7
Showing how round planes can form undercut profiles







Figure 8
Stages in removing waste (with tablesaw or rabbet planes) before finishing moulding with hollows & rounds



the wood being planed. It will make your task much easier if you start with knot-free wood and plan to cut the moulding with the grain, as shown in *figure 6*. Difficult material may be worked with very sharp irons and by taking very thin shavings. Extremely hard wood is best worked with planes that have more steeply set irons.

Despite these potential difficulties the

hollow or round is actually more versatile than a specific moulding plane or a particular router bit or shaper cutter. It doesn't have to match the required profile perfectly, and neither is it limited to a profile of the same width as its iron. Even undercut moldings are possible with hollows and rounds (figure 7), and the process is complemented by the use of trimming planes such as side snipes and

snipesbills (special forms of rabbet planes designed to clean up the sides of steps, quirks and grooves). If you're not lucky enough to own any of these exotics, you can do much of the same kind of work with the more common, small, metal, side-rabbet planes, a double-ended version of which is still sold by Stanley<sup>TM</sup>. Nevertheless, any use of the hollow or round is made easier if as



Circle #107 on Resource Directory Coupon



MONEY BACK GUARANTEE

# How I Turned My Hobby Into A Successful Craft Business!

With an RBI HAWK ULTRA Precision Scroll Saw.

When it came time to purchase a new scroll saw, I knew I wanted the best. So I purchased an RBI Hawk Precision Scroll Saw.

With my RBI Hawk
Precision Scroll Saw,
I now produce the woodworking projects I have
always dreamed of creating
and my customers

rbindustries
The American Tool Manufacturer
1801 Vine St., Harrisonville, MO 64701

RBI Hawks are designed and made in the USA for the professional shop and demanding hobbyist. With three sizes to choose from, we have the saw that's just perfect for you.

after year.


will treasure...vear

Susan Bailey, CA

To Order *or* For Your FREE Brochure, Call 1-800-487-2623.

# Spend More Time WOODWORKING And Less Time Shopping...

with help from the newest edition of Woodworker's Source Book. In this time and money-saving resource you'll discover hundreds of listings of tool manufacturers and discount suppliers; plus information on courses, magazines, furniture plans and more. You'll order with order



more. You'll order with ease using the company names, addresses, and 800 numbers included. Order today and end those frustrating, time-wasting searches for tools and supplies! #70281/\$19.99/160 pgs

| YES! Please send mecopy(ies) of <i>The Woodworker's Sourcebook</i> (#70281), for \$19.99 each. Add \$3.50 postage and handling for the 1st book; \$1.00 for each additional book. Ohio residents add 5.5% sales tax. Allow 30 days for delivery. |   |              |          |  |  |
|--|---|--------------|----------|--|--|
|  | VISA/MASTERCARD ORDERS CALL<br>TOLL-FREE 1-800-289-0963 |              |          |  |  |
| Payment  | enclosed S  | š            | (or)     |  |  |
| Charge my  | □ Visa  | ☐ MasterCard | Exp.Date |  |  |
| Acct. #  |   |              |          |  |  |
| Signature_   |   |              |          |  |  |
| Name   |   |              |          |  |  |
| Address  |   |              |          |  |  |

Zip


3187

Send to: Betterway Books 1507 Dana Avenue • Cincinnati, Ohio 45207

City

State

# Tried & True




much waste as possible is first removed by other guided tools (figure 8).

An arris may be worked directly with a hollow plane, centering the plane over the corner and holding it while working so that the lines indicating the extent of the required roundness are approached evenly. Using a round plane on an arris requires first beveling the comer so that the plane has a flat surface to start on. Using your fingers as a fence, cut a small hollow in the center of the flat at the far end of the work, as shown in figure 9. If you mark a line down the center of the flat first, guiding the plane along this line is no harder than guiding a parting tool or other carving tool along a marked line. With each successive stroke start further back until the entire length is under the plane. By varying the angle at which the tool is held, you'll be able to approach one or the other lines marking

the extent of the required hollow.

Since hollows and rounds can be used to form round-overs and coves of various sections it should be obvious that they can be used to trim similar sections of other profiles (figure 10). A small hollow plane, for example, is an excellent tool for repairing or trimming a beaded edge and can be used where continued use of the beading plane would be prohibited by virtue of its quirk. As to which sizes work best for any given profile, preference will vary with experience. And remember, holding a round plane skewed to the line of work will increase the width of the hollow being cut, just like passing a piece of wood diagonally over the tilted blade of a table saw. PW

**Graham Blackburn** is a contributing editor to Popular Woodworking who builds furniture and writes about woodworking in Woodstock, New York.





#### BUCKBOARD BENCH KIT REAL SPRINGS


Kit includes authentically designed steel springs that give a little. Metal arms and back-rails, complete hardware and detailed instructions. New-full size patterns. \$49.00 includes shipping UPS.

SPECIAL: Purchase 2 kits for \$90.00

PECIAL: Purchase 2 kits for \$90.00 The Roudebush Co. P.O. Box 348 Star City, IN 46985 VISA/MC accepted 800-847-4947.

Circle #108 on Resource Directory Coupon

all of your issues of Popular Woodworking in a handy, durable binder. Just \$11.95 postpaid. (OH res. add 5.5% sales tax). Outside U.S. enclose \$13.95 in U.S. funds. Send check or money order to: Popular Woodworking, Binder Editor, 1507 Dana Ave., Cincinnati, Ohio 45207.



Circle #101 on Resource Directory Coupon

# Curly Maple Country Wall Shelf

A table saw, router and a few basic hand tools are all you'll need.

# By Steve Shanesy

here are many reasons for the current popularity of country furniture. It not only reminds us of simpler times, but its casual elegance helps produce a friendly, informal setting where we can relax and retreat from the hustle and bustle of our busy, modern world. But these country-inspired styles hold additional appeal for the cabinetmaker, especially those of us with limited time and machines, because like their original antique cousins, country pieces are relatively simple to build with basic tools.

Country cabinetmakers of the colonial era might have been farmers with time on their hands in the winter months. Not being professional tradesmen like their city counterparts, the country cabinetmaker combined simple joinery and a modest assortment of tools to build the fumiture for his home. Although I used a table saw and router in constructing this wall hung shelf, it's not difficult to imagine doing all the work with a hand cross-cut and rip saw, a chisel or two and a couple of basic hand planes.

With a nod to the past, I included an element or two that puts this project in

the antique reproduction category, such as using cut nails and not only dovetailing the top rail and drawers, but using a bevel-edge drawer bottom as well.

# **Prepare the Stock**


Although it's expensive, I selected curly maple, because little wood is required for the project. Cherry or even poplar would also make good choices. And since figured woods such as curly, fiddleback or tiger maple are expensive, I mixed in regular maple in the places where the wood really wouldn't be seen. And, I used a less expensive secondary wood for my drawer sides, back and bottom.

Before starting in the shop, I made up my cutting list. I always





**Photo 1** The assembled dovetail on the top rail joining the case side. The top edge, hidden by the crown, was not dovetailed, but simply nailed to the side.



begin with an accurate, detailed cut list, which was especially helpful in laying out the cutting of the three curly maple boards from which I had to get all my pieces. I was able to plan where the best figure would be showcased in the project and make sure grain direction was balanced and pleasing to the eye.

Since the maple I bought was already surfaced to ¾", the only rough preparation required was to straighten the edges on the jointer. I then cut all my pieces to width and length according to my cutting list. I did, however, put off cutting the crown molding miters and drawer fronts until the case was assembled. As with all projects, cut like parts on the same set-ups to maintain consistency and accuracy. Just remember that you'll have rights and lefts, ups and downs, as you proceed through your cutting.

| No.        | Letter | Item          | Dimensions            | Notes   |
|------------|--------|---------------|-----------------------|---|
| 2          | A      | Sides         | ¾" x 7" x 33¾"        | Rabbet top edge, dado for shelves   |
| 01         | В      | Тор           | ¾" × 7" × 32½"        | Rabbet two long edges   |
| 01         | С      | Bottom        | ¾" x 7¾" x 34½"       |   |
| 2          | D      | Shelves       | ¾" x 7" x 32"         | Run plate groove before<br>assembly, dado bottom shelf<br>for drawer partitions |
| 01         | E      | Front Rail    | ¾" x 3" x 33"         | Half dovetail to sides  |
| 01         | F      | Back Rail     | ¾" x 3" x 31½"        |   |
| 02         | G      | Partitions    | ¾" × 5½" × 7"         |   |
| 02         | Н      | Plate Rails   | ¾" x ¾" x 31½"        |   |
| <b>3</b>   | 1      | Drw. Fronts   | ¾" x 5¾6"x 91¾6"      |   |
| <b>a</b> 6 | J      | Drw. Sides    | ½" x 5¾6"x 6¾"        |   |
| 3          | K      | Drw. Backs    | 12" x 411/6" x 915/6" |   |
| 3          | L      | Drw. Bottoms  | ½" x 6%6"x 9¾"        |   |
| 02         | М      | Side Cm. Mld. | ¾" x 3" x 9"          |   |
| 01         | N      | Fmt. Cm. Mld. | ¾" x 3" x 36¾"        |   |
| <b>3</b>   | 0      | Wood Pulls    | 1" diameter           |   |



Photo 2 Before assembly, the plain maple bottom is edged with curly maple then chamfered using a router.



Photo 3 The crown compound miter is cut on the table saw. Tilt the blade to 30° and the miter gauge to 35°.



Photo 4 A simple method for "clamping" the crown when gluing is using masking tape—just pull it tight over the joint.

# Mill the loints

Before leaving the table saw, I cut my ¾" x ½" deep rabbets on the top ends of the two side pieces and on the long edges of the top piece using a dado set. I then made my ¾" x ¾" deep dado cuts in the sides (to hold the two shelves), and on the bottom side of the lower shelf (to house the two verticals that form the partitions between the three drawers).

Before assembly, I routed a "plate groove" (see diagram 1) on each shelf top surface, and hand-cut the dovetails and pins for the top front rail where it joins the sides (the back rail butts to the sides and is nailed in place). Since the front rail extends to the top rabbet, only the bottom half of the dovetail required cutting (photo 1).

Part of my stinginess with the curly maple included making the bottom from regular maple, which I edged with one inch wide by ¾" thick curly maple. An added benefit was that no end grain showed on the bottom and the curly grain is especially striking with the bevel detail (photo 2) on the sides and front. When gluing the edges, a spline or biscuit is required for the end grain of the bottom but unnecessary for joining the long grain to long grain front edge. It's important to rout the bevel detail before assembly.



Unless you want to hold parts in place while assembling, clamps are not required, since all joints are nailed using the antique-looking square cut nails. In fact, you could make a case for eliminating glue as well,

but gluing is an old habit of mine that's hard to break.

First assemble the lower shelf and drawer partitions. Since these are nailed from the top down, it's easier to swing a hammer now rather than when it's assembled with the sides and upper shelf. The cut nails are anything but delicate, and with their wedged shape, are prime candidates for causing splits. I overcame this potential hazard by drilling a pilot hole for each nail. It's also important to consider a nice spacing arrangement for the nails, rather than just accepting arbitrary, approximate locations (Just because you're using nails doesn't mean it's not furniture!).


The sides, shelves and top came next. Each was set in its

dado or rabbet and nailed. I then attached the front top rail in its dovetail and nailed it where it sits in the rabbet of the top. I likewise nailed the back rail in its rabbet, and also nailed it through the side. With this complete, I was then able to turn the piece upside down to set the bottom in place and nail it. I used two nails each for the sides and drawer partitions. Again, I drilled pilot holes for each nail.

# Make and Attach the Crown

Everything having to do with the crown molding was done on the table saw. Its shape was made by simply making two 45° angle cuts, one for the bottom and one for the top (diagram 2). Before cutting, however, I laid out the profile of the crown and quickly concluded that an extra triangular shaped piece would be needed on the backside to create sufficient flat to nail it easily to the case. This was accomplished simply enough by cutting an equilateral triangle with ¾" legs. This was glued (not nailed) in place so that it lined up with with angle cut on the bottom edge .

After cutting the angles on the long edges of the board (giving the crown its final profile), I cut the compound miters where the sides of the crown meet their corresponding front. This was accomplished easily enough on the table saw by setting the blade to a 30° angle and the slot miter gauge to 35° (photo 3). With careful measurements and thoroughly thinking through the cuts (I had to be careful; it was working with the last piece of curly maple in the shop!), the crown parts were complete. To attach the crown to the case, I nailed the parts on with the bottom of the crown one inch down from the top of the case. To pull the compound miter joint together, I used a





**Photo 5** Drawer sides were joined to the front and back using  $\frac{1}{2}$ <sup>n</sup> half blind dovetails cut on a dovetail jig.



**Photo 6** The drawer bottoms are %" thick but are beveled to slip into a %" groove, a traditional drawer construction method.



**Photo 7** A stopped groove was required on the inside of the drawer front to receive the bottom. It was cut with a router.

few pieces of masking tape (*photo 4*) — much faster and simpler than cutting clamping cauls to just the right shape, which would be an absolute requirement if one were to use clamps to do the job.

# **Cut and Assemble the Drawer Parts**

All three drawers are the same size. The curly maple fronts were cut from the same board and kept in sequence so that the grain matched across. The sizes provided in the cutting list are for half-inch sides, backs and bottoms with a ¾" inch front. I used half-blind dovetails for joining the sides to the front and back. If you use a different construction method, your sizes will change, except for the drawer openings.

We recently equipped our shop with a Porter Cable dovetail jig outfitted with a template for making half-inch dovetails and box joints (*photo 5*). Although these, and most other jigs, take a bit of precise set up, they produce nice, repetitious results. For this project, I would have preferred their template that makes 2" dovetails because these would have given a more "hand cut" look. But as is, I'm satisfied with the look achieved using the half-inch template.

The drawer bottoms were made in the traditional style of a bevel edged panel (*photo 6*). The bevel is cut in the same manner as raised panels on the table saw. Simply tilt the blade to about 15° and run the panels on edge. Calculate the fence setting so that the bevel you make fits nicely into a %" x %" groove that starts %" from the bottom edge of the drawer sides and front. Using half blind dovetails required me to make a stopped dado for the drawer bottom groove in the drawer front. To mill the dado, I used a router set up on the router table with a %" straight bit (*photo 7*). I trimmed the back so that its width is %" narrower than the sides, which allows the bottom to slip in from behind. The drawers are small enough to slip simply in and out of their openings with no guide system required. For pulls, I purchased turned round knobs at the local hardware store.

#### **Finishing**

Since the parts were pre-sanded to 120 grit before assembly, I picked up the sanding chore using 150 grit with the random orbit palm sander. I proceeded to 220 grit and finished sanding by breaking all the sharp edges with 120 grit sandpaper.

Since I wanted the shelf to look as if it was already a number of years old, I mixed brown and yellow aniline dye stain to give it a honey color, the approximate color a shellac finish on maple might attain after years of exposure to light. To avoid the splotchiness of maple and stain, I sprayed the aniline dye stain and immediately wiped it down with lacquer thinner on a clean rag. This evened the color for good consistency.

I topped the color with a water based lacquer that I sprayed on. After the first coat dried for about 45 minutes, I sanded it with 360 grit paper, then sprayed a second wet coat. It dried to a smooth finish. To create a little contrast, I sprayed the pulls black using black lacquer from an aerosol can and then topped them with a coat of clear lacquer.

Steve Shanesy is editor of Popular Woodworking.

Collector Coffee Table

**Proudly display** your small collectibles for all to enjoy.

By Steve Shanesy

hether they're matchbooks or model cars, pocketknives or postcards, memorabilia from family history, or simple reminders of shared vacations, most of our collected objects too often wind up boxed in

the attic or pushed to the back comers of dresser drawers. And since it seems that just about anything can be a collectible these days, why not display your treasures? The currently popular "collector's table" is a practical and convenient way to display both your private collection and your woodworking skills.


be completed in just a couple This table project can customize it to fit your collecweekends. Plus, you can that it's primarily a table saw tion. A second benefit is project. Although I used a bench top mortising machine and table saw tenoning accessory tool, these are not essential to completing the project.

Since my table was made with no specific collection in mind, the size was determined by simply considering a nicely proportioned coffee table with reasonable glass top display area. 🚡 My table overall is 40"x24"x16" (diagram 1). Using 4"-wide stock for my top frame, my glass "viewing" area for the glass top is 16"x32". The width of the top frame is important because, simply in addition to looking right, it must be wide enough to cover the leg and apron, as well as the top edge of the display tray below (diagram 2).



At left, three generations of memories make an attractive and personal display. Photo 1 Above, cutting mortises in the table legs.











Diagram 1





# Milling the Parts

I had enough four quarter red alder left from a previous project to build this one, but I wanted a 1%" leg thickness, and that posed a problem. My first task after cutting my material to rough length was gluing up the %" thick stock to make my legs. While these pieces were drying, I cut my other material to size (see cutting list). Since I planned mortise and tenon joints for the legs and aprons, my finished apron length was the distance between the legs plus 1%". With the leg material dry, I squared the pieces to 1%" and trimmed them to their final length of 15%". Although the legs were to be tapered in the Hepplewhite style, they first had to be mortised (photo 1). Before using the table top mortising machine, I carefully laid out which faces of the legs were to be machined and the location of each mortise. Although classified as a hardwood, alder is relatively soft,

| Schedule of Materia  No. Part Item |   |                | Is/Collector's  Dimensions | Notes                |  |
|------------------------------------|---|----------------|----------------------------|----------------------|--|
| 04                                 | A | Legs           | 1%"x 1%"x 15%"             | taper 2 inside face  |  |
| 02                                 | В | Aprons, long   | 3/"x 4"x 351/4"            | incl. 2, 3/" tenons  |  |
| 02                                 | C | Aprons, short  | 3/"x 4"x 19/4"             | incl. 2, 3/11 tenons |  |
| 02                                 | D | Top frame      | 3/"x 4"x 40"               | miter 2 ends         |  |
| 02                                 | E | Top frame      | 3/"x 4"x 24"               | miter 2 ends         |  |
| 02                                 | F | Tray sides     | ½"x 3%"x 33½"              | rabbet ends          |  |
| 02                                 | G | Tray sides     | ½"x 3½x 17"                |                      |  |
| 01                                 | Н | Tray bottom    | 1/4"x 171/6"x 33"          |                      |  |
| 04                                 | 1 | Dowels         | ½"x 1½"                    |                      |  |
| 06                                 | 1 | Nesting blocks | 1"x 3"x 3½"                | taper top 2"         |  |

# **Supplies**

| Q1   | Glass top    | 3/4"x 161/4"x321/4" | bevel edge |
|------|--------------|---------------------|------------|
| 04 K | "L" brackets | ½" x 2"             |            |



Photo 2 A table saw tenoning assessory is a safe and accurate method for cutting tenons. Since the leg and apron are flush, a precise set-up is important.



Photo 3 The table leg inside faces were tapered on the table saw using an adjustable tapering jig (see Make Your Own Adjustable Tapering Jig). The easy to make jig (about 30 minutes) produces safe, accurate cuts. You'll use it on many future projects, too!

# **Equipment Required:**

Table Saw, Mortiser or Doweling Jig or Biscuit Jointer, Drill, Clamps.

# **Optional Equipment:**

Table saw tenoning accessory, router with panel raising bit, bench plane, dowel centers, finish sander, HVLP finish sprayer.





Photo 4 "L" or corner brackets are used to support the removable display tray. To accurately postion them, clamp a block under the apron, set them in place and fasten to apron. Photo 5 Nesting blocks keep the tray in postion. They are tapered for easy placement and removal of the display tray.

which makes using the hollow chisel mortiser a breeze. From layout to cleaning up the mortises with a hand chisel, all eight mortises were complete in about 15 minutes. Other options for joining the legs and aprons include, but are certainly not limited to, doweling and biscuit joining.

I next cut the tenons (photo 2), paying close attention to setting up the table saw tenoning accessory. Since the aprons are flush to the legs, the set-up had to be very precise to make the waste from the tenon cheek exactly the same as the dimension from the face of the leg to the mortise, in this case, %". After cutting the tenon cheeks, I cut the tenon shoulders square and to the exact length and depth on the table saw, using the fence and slot miter gauge in combination.

The last machining task before gluing the base together was cutting the tapers (photo 3) on each inside face of the four legs. This job was quickly accomplished using a shop built, adjustable tapering jig (see sidebar).

After dry fitting the base parts, I glued them together. When dry, I attached both the "L" brackets (photo 4) to support the display tray and the "nesting" blocks (photo 5) to position it. The nesting blocks are tapered leaving about a half inch of flat at the bottom so the tray glides easily into position.

# Make the Top Frame

The top was first mitered at the ends using the slot miter gauge on the table saw (photo 6). Carefully check a test piece to make sure your cut is a true 45°. It's equally important to make sure your saw blade is set square to the saw table top. After cutting the miters. I milled the rabbet in the top inside edge of the frame for the glass (photos 7 & 8). I cut this rabbet after the miters because if done in reverse, the probability of tearing out that last little bit of material at the top of the rabbet is too great. The rabbutt hinge and a lid support as an adjustment mechanism. Make the jig long enough to taper various lengths, from coffee to longer dining table legs. The "arms" for our jig are 1"x3"x 35", a good length for most leg tapering needs.


to take the headache out I of cutting tapers and to add a great jig your shop collection, make this adjustable tapering jig. All you need is some scrap lumber, an old

When cutting these pieces,



bet dimension is ½" wide x 16" deep. The width dimension is arbitrary within reason, but the depth is determined by the type of glass you choose for the top. For a great looking top, I ordered my glass with a faceted, or beveled edge. It really dresses up the piece! I learned from the glass supplier that the %"-thick glass, when beveled, would have 1/4" of edge thickness left. I made the rabbet another \%" deep because I like to slip pieces of clear vinyl of the same thickness under the glass in the rabbet as a soft pad. This will bring the bevel edge flush to the wood edge.

Before gluing the four-piece top together, I biscuit jointed the corners to reinforce the miter joint (photo 9). Be sure to place the biscuit slots closer to the inside comer of the joint so you don't risk exposing the hidden joint when milling the long, beveled profile on the top's outside edge. The top was then glued and clamped together (photo 10).



# Make Your Own Adjustable Tapering Jig



be sure the arms are milled straight and square. Before attaching the hinge, make any necessary preparations for the lid support. Be sure to chose a support that'll lock in place easily. We used a Brainerd™ Standard lid support, and cut a notch in one arm opposite the hinge end to properly attach it. On the ouside of that same

piece, we fastened the stop block to support the work as it is pushed through the saw.

When using the jig, the thickness of the leg, the amount of taper and length of leg determine the saw fence and jig angle setting. The set-up will only take a minute and your results will be very rewarding.

I chose a long bevel for the top's edge detail. It echoes the bevel of the glass top as well as the angular taper of the legs. To mill the profile, I used a panel raising router bit (photo 11). Since this router bit was made to leave a tenon on a panel edge, I had to modify the profile by hand planing the squared off tenon to leave a long, smooth bevel (photo 12). An alternative method to routing the profile would be to saw the bevel edge on a table saw, using the same procedure as raising panels on a table saw. Set the blade angle to about 15°, adjust the fence to the setting you want and run each piece on edge.

Although the top is removable by simply lifting it off, glass and all, it still needed a method to keep it in place and not slide on its base. A simple solution was employed using short dowels (photo 13). I first crossed pencil lines on the top of each leg to find the center. I then drilled a ½" diameter hole about ¾" deep. Next, I placed a 1/2" dowel center in each of the four holes, one for each leg. After carefully positioning the top on

# WARNING

When operating a biscuit jointer, always turn the machine on before positioning it on the work. This safety precaution reduces the risk of the machine "climbing" up your arm. If you attempt to start it with the blade contacting the work, the possibility of climbing is much greater.

the base so overhang was equal all around, I pressed the top down hard over each leg to dimple the underside of the top, thus giving me my exact hole drilling locations. I decided to glue the dowels in the top instead of the legs, because the protruding dowels under the top would provide a handy space for my fingers under picking it up with the glass in position. Before gluing the dowels in place, I tapered their length so that locating them in their corresponding leg holes would be a simple task.



Photo 11 Most of the top edge profile was cut using a panel raising router bit. Cut the profile in three passes since you're removing substantial material.



Photo 12 Because the panel raising bit left a tenon, the bevel profile was finished usina a bench plane.

# Assemble the Display Tray

The display tray is basically a drawer that doesn't slide. To make it, I used ½" birch plywood for the sides and ¼" tempered hardboard for the bottom. Since my plan was to paint the tray, the colors and materials didn't matter, as long as they'd take a paint finish well. The tray is sized so it's no deeper than the aprons and allows a 1/8" clearance at the inside corner of all four legs. The joinery is simple rabbet joints on the two long sides, which are ¼" deep x ½" wide. The bottom



Photo 13 Dowel centers were used to locate the mating holes which position the top on the base.

fits in a ¼" x ¼" groove that starts ¼" up from the bottom edge of the sides. The sides were glued and nailed together, slipping the bottom in place before the fourth side was fastened.

# Sanding and Finishing

Alder sands easily and I used a a random orbit palm sander taking it to 220 grit. I did the same for the birch tray sides. After breaking the edges, I painted the tray with a cream colored latex paint. I wanted the tray's painted finish to remain clean and fresh, so I protected it by spraying two clear top coats of water based lacquer. This "barrier" finish will make finger prints clean up nicely, will prevent the paint from "bruising," and will keep all but the deepest scratches from marring the paint color. While clear coating the display tray, I spray finished the alder with the same water based lacquer. I used an HVLP (high volume, low pressure) sprayer that significantly reduces both fumes and overspray. I sanded the the first coat of lacquer with 360 grit paper, knocking down the raised grain and preparing the surface for a final, wet coat of lacquer.

Steve Shanesy is editor of Popular Woodworking.


# **Turnings**

on the Table Saw

If you haven't taken the step toward a lathe, let your table saw do the job.

any woodworkers have managed to reach a certain skill level without having to come near a lathe. Still, there are certain projects that require turning to be considered really finished. If a lathe isn't part of your shop, you probably believe that your only real alternative is to purchase a pre-turned piece for your project. However, if you would like to make your own simple turned pieces, but you aren't ready to tackle the lathe, this project will offer another alternative.

The unusual device discussed in this story was originally designed to work on a Delta 10" Unisaw, but the design can be altered to fit any table saw. The jig gives you the opportunity to perform simple turnings on your table saw. Though it wasn't designed with mass production, a set of four legs of any length and diameter can be cut and sanded in about ten minutes.



Convert square stock to round using your table saw and this jig (left). Bolt on your disk sander attachment to your saw arbor (above) and you can sand the work, too!

# Making the Jig

After determining the length jig desired, cut the two sides of the ripfence tunnel (B) to length and slightly higher than the rip fence itself. Place a strip or two of masking tape on both sides of the saw's rip fence. Run the tape the entire length of the fence to act as clearance shims (two thicknesses of ordinary typing paper will also work). With the paper or tape in place, C-clamp the two side tunnel pieces (B) to the rip fence. Then cut the tunnel top (A) and fasten to parts (B) using glue and countersunk screws (diagram 1).

Lay out the jig's handle from one of your favorite handsaws. Cut to shape and carefully sand all hand-contact surfaces. You may want to chamfer or roundover the edges to make the handle even more comfortable. Secure the handle in place by countersinking two screws up through (A) into the handle, again using glue.

Cut the tapering arm (C) to length and width. The tapering arm will require a ¾" wide groove running down the center of one 3¾" face. The groove, cut all the way through the piece, starts approximately 2" from the far end and stops 6" from the near end of the piece. Cut the groove by drilling two ¾" holes,


lay out the tangent lines between them, and use a scroll saw, coping saw or sabersaw to carefully cut the lines. Then use a file to clean the sides of the slot. Make sure the edges are smooth so the carriage bolt will slide freely without becoming snagged when adjusting the size of the workpiece.

Next cut two strips (D) to form the dovetail channel. Each piece will have one edge beveled at 15° as shown. These are secured to the slotted part (C) with glue and screws. (C) can now be attached to (B) with a 3" butt hinge, preferably with a non-removable pin.

Using a good grade of  $\frac{1}{2}$ " plywood, lay out the angle adjuster (F) as shown in **diagram 2**. This is secured to the top edge of (C) with glue and screws.

The angle adjuster (F) is attached to the top of (A) with a  $\frac{1}{2}$ "x 20 hanger bolt, washers and wing nut. (Note: A hanger bolt is half woodscrew thread and half machine thread.)

Cut out parts (G), (H), (I) and (J) (diagram 3), which will become the adjustable tailstock and the stationary headstock. Note the outer corner of (I) is beveled. Attach (G) to (H), and (I) to (J) with woodscrews and glue. Notice that angle brack-



Some of the many turning styles you can produce on your table saw using this jig are displayed above. These include short and long, square or round tapers, straight columns, round taper with square shoulder, and double-end taper.

Qty. ThxWxL Notes 0 34" x 21/2" x 42" A 1 Ripfence tunnel top 34" x 3" x 42" B 2 Ripfence tunnel sides C 1 34" x 334" x 42" **Tapering Arm** 34" x 1" x 42" **Dovetail channels** 0 D 2 E 1 ¾" material Handle 0 F 1 ¾" plywood Angle adjuster G 1 34" x 31/2" x 5" Tailstock block H 1 34" x 314" x 31/2" Tailstock block T 1 34" x 31/2" x 31/2" Headstock block

34" x 414" x 31/2"

34" x 34" x 4"

1/4" x 4" x 32"

OL long. Insert each part in a drill press or bench mounted drill motor and, using a **Hardware** metal cutting file, sharpen one end to a

point. If at all possible, these tips should be heat treated and hardened since they

ets (M) are cut into all the pieces to

mount flush with the surface. This can

be accomplished using a router table, or

a dado stack mounted on your table

saw. Attach all the angle irons as shown,

and countersink all screws flush with the

surrounding surfaces to prevent any

pieces of threaded rod 1/4" x 20, about 2"

Parts (R) and (S) are similar and are

binding. File or sand flat if necessary.

take a lot of friction wear.

If heat treating is not possible, the tips will hold up remarkably well if kept well lubricated with bar soap, paraffin wax or beeswax. Remember, these tips fit into T-nuts which will become the bearing surfaces of each end of the workpiece. Mount parts (R) and (S) through the angle braces and blocks (1) and (H) using nuts and washers as shown. Attach the four angle braces (N) to the blocks as shown.

Cut out two dovetail blocks (K). One is fastened to block (J), which is then fastened with glue and screws to parts (C)

1

0 K 2


1

Carriage bolts, threaded rod, jam nuts and washers, butt hinges, hanger boits, wing nuts and washers.

Headstock block

**Dovetail blocks** 

Lexan Shield



and (D), as shown in the drawing. The other is fastened to block (G) and the finished tailstock assembly is slid into the groove formed by (C) and (D) (diagram 4). Make sure K slides freely within the slot. This and other parts should be thoroughly coated with clear lacguer (sever-

> al coats) or urethane for a hard slippery surface.

> When assembly is complete, use steel wool and a hard carnauba paste wax on the entire sliding area. A coat of silicone lubricating spray will also help reduce friction. The underside of the tunnel portion of the jig is treated the same way. Be sure to remove any paper or masking tape from the saw fence, as these could cause binding.


> Lexan provides an unbreakable shield to protect the operator. This should be purely a precaution. In all the years I've used this jig, I can't recall a single time when the workpiece flew out of the jig.

# To Use the Jig

Before using the jig, set the adjustments on the saw itself, including the height of the saw blade (which, incidentally, must be sharp and have a good set), and the alignment of the rip fence,







At far left, the blank is chucked in the turning fixture and is ready to run. (Center) After several passes, the tapered round form is mostly complete. At left, the table saw blade has been exchanged for a sanding disk attachment that removes saw marks and sands the leg smooth.

which must be locked down securely.

If making a tapered leg, taper the square stock prior to turning, and drill a hole in each end to accommodate a metal T-nut, which will act as a bearing surface. The workpiece is mounted between the centers of the shop-made jig. Don't forget to lubricate the turning centers with your choice of lubricant, keeping in mind that oil is not heavy enough to do the job.

Any length up to the capacity of the main jig can be set. Open the tapering arm far enough to make the taper on the size workpiece you want, making sure the blade and sander disk will clear the jig centers on both ends of the unit. The small end of the tapered leg should be at the far end, and the wider diameter at the near end.

The same process holds true for cutting cylinders. Make the square block into an octagon, then permit it to spin around by the blade. In each case the workpiece will have to be moved slightly with the saw fence, closer to the blade or sanding disk for best results. Remember, don't force the work, and don't try to push too fast. Let the saw do the work.

When cutting a stop taper, set up a block or some sort of

accurate mark to shoot for. When you reach that point, turn off the saw and remove the workpiece. When cutting a reverse taper (narrow at both ends and thick in the middle) follow through and make the first cuts and sand these. Then turn the workpiece end over end and cut the other half of the reverse.

You may want to make a wedged shaped push stick to act as a kind of brake to slow down the speed of the turning workpiece. One has to remember that a table saw blade turns at about 115 miles per hour. The workpiece as a result can spin quite fast, but if properly mounted between centers, there is little danger the workpiece will come off. Remember, be sure to review your basic

Remember, be sure to review your basic saw safety rules: Stand to one side, not directly in line with the workpiece. Wear your goggles. Know where your hands

and fingers are in regard to the saw blade. Use only sharp saw blades and work slowly. Don't force your work.

Diagram 3


STATIONARY HEADSTOCK
DETAIL (DRAWINGS NOT
TO SCALE)

JAM NUTS


ANGLE IRONS D


JAM NUTS


ROD 2" LONG @



**Don Kinnaman** is a retired shop teacher and woodworker who lives in Phoenix, Arizona.







ndian Summer is the perfect time of year to sit on your porch swing watching the leaves turn as summer slowly slips away. You say you don't have a porch swing? Well, there's still time to build one!

We've come up with a design that will be the envy of your neighbors, and this swing will last a lifetime. Thinking economically, we chose poplar, since it provides excellent strength and stability, yet keeps the price for the project at an acceptable level—about \$100 including all the hardware and paint!

Because of the sweeping curves used for the sides, there is a certain amount of template work to be done. We've included full-sized plans for these pieces in the PullOut Plans™ section, which should take the head scratching out of this project. The first step in constructing the swing is to use these plans to cut out the shapes for the seat ends, back ends, arms, arm supports, seat center support and the slat support block. If you have access to a planer, the lumber for these pieces should be run to 1½" thickness, if not, ¼ surfaced lumber can be purchased from you local hardwood lumber supplier. There may be some measurement adjustments necessary, but it shouldn't affect the overall design.

There are a couple of options available for shaping the parts to match the plans. We've shown three options in the sidebar Duplicating with Templates. The method you use will be determined by the equipment in your shop.

You will note that the tenons for the back ends are shown with a dotted line inside the darker line on the plans. This is so the rough size and angle of the tenon can be determined. The finished tenon should be made after the mortise is cut to ensure a snug fit.



Photo 2 A 1/2" bit chucked in the drill press is used to chain drill the mortise in the seat end removing most of the waste. Although a standard twist drill will work, a brad point spur or Forstner bit is better.



Photo 3 The mortise is then cleaned up and squared by hand using a chisel. This hand work cleans up the cheeks and bottom giving this half of the joint its accurate dimension.



Photo 4 Before gluing, the back and seat end pieces are dry fit. Looks like the mortise and tenon are a good fit!



Photo 5 Pinch dogs were used to pull the joint tight. Though this leaves small holes in the work surface, it avoids the difficulties involved in clamping curved and angled surfaces. These inexpensive tools are extremely handy in many situations.



Photo 1 The pieces that will form the ends of the swing have been shaped to match the templates from the PullOut Plans.

**Tools Used, Not All Required** Table saw, bandsaw, spindle sander, router, random orbital sander, %" drill, doweling jig, %" roundover router bit, 1/2" x 1/2" rabbet bit, champher bit, 1/2" drill bit, dowel centers

Once your pieces are shaped (Photo 1), the next step is to cut the two mortises in the seat sides. Since there are only two, we decided to cut them by hand. Begin by laying out the location for the  $\frac{1}{2}$ " wide x 2" long mortises as located on the PullOut Plans. Drill out the mortise using a 1/2" bit (a Forstner or brad point spur bit is ideal) in a drill press (Photo 2), then chisel to a depth of 11/2". A beautiful mortise isn't critical because the shoulder of the tenon will hide minor imperfections, so if you've been waiting to try a hand-cut mortise, this is your chance (Photo 3). They should take about 15 minutes each.

Once the mortise is finished, use the PullOut Plans to locate the tenon on the back ends. Cut the tenons a little oversized on the bandsaw to allow fitting. The shoulders are the most critical part of this step, and may require some judicious fitting

When satisfied with your tenon fit, sand the pieces as necessary to 120 grit. Now, glue and clamp the sides. You may have difficulty clamping these pieces due to their angles and curved nature. We benefited from our painted finish by using pinch dogs to pull the joint together (Photo 5). If your finish is clear, you may require a clamping caul to put pressure in the right places.


The next step is to attach the arm supports to the arms using ½" dowels (Photo 6). Once again the placement for the supports can be copied from the PullOut Plans. We used a doweling jig to locate the centers of the ends, and once drilled, glued and clamped the pieces and set them aside to dry.

There are two routing steps necessary for the sides. A ½" x ½" rabbet must be cut on the top inside edge of each side for the seat slats. Again, the position of the start and stop point for each rabbet is indicated on the PullOut Plans. We used a 1/2" x 1/2" rabbet bit with a pilot bearing to make the cut. The bit leaves rounded stop and start points, so it's necessary to square these up with a chisel (Photo 7).

The second routing step is a %" roundover to soften the edges of the sides and arms. We decided not to run all the edges with this profile. We ran the entire outside edge and the top "ball" on both edges for the sides (Photo 8). On the arms, only the top inside and outside edges were run.

Once you've finished these routing chores, set these pieces aside and move to the rest of the swing frame. Cut the seat's center support, rear and front stretchers and the back top stretcher according to the materials list. While at the saw, set the blade to 12° and cut the top edge of the front seat stretcher at this angle. Once cut, the bevel will allow the seat slats to lay in the end rabbet without running into the previously squared edge of the front stretcher.

The back top stretcher has roundover router passes on three of the long edges. Again, use the %" roundover bit with the



pilot bearing. The other edge has an  $\mbox{\ensuremath{\%}}"$  chamfer where the fourth long edge meets a back slat.

The next step is to locate the positions for the ½" dowels used to join the seat frame and top stretcher to each other and the sides. First drill dowel holes in both ends of all four pieces *(Photo 9)*. Don't worry about matching the locations in the sides at this time.

We used a set of dowel centers (*Photo 10*) to locate the positions for the dowel holes in the front and rear seat stretchers and in both sides. Again, the PullOut Plans indicate the stretcher locations. Start with the middle seat support, which runs between the front and rear seat stretchers. Make the seat support flush to the top of the front stretcher, and flush to the bot-

| Sche     | Schedule of Materials |                    |                      |  |
|----------|-----------------------|--------------------|----------------------|--|
| No.      | Letter                | Dimensions         | Item                 |  |
| 02       | Α                     | 1½" x 6" x 25"     | Seat ends            |  |
| 02       | В                     | 1½" x 5" x 28"     | Back ends            |  |
| 02       | С                     | 1½" x 3½" x 21"    | Arms                 |  |
| 02       | D                     | 1½" x 3½" x 11"    | Arm supports         |  |
| 01       | E                     | 1½" x 3½" x 151¾6" | Seat center support  |  |
| 01       | F                     | 1½" x 3½" x 60"    | Seat rear stretcher  |  |
| 01       | G                     | 1½" x 3" x 60"     | Seat front stretcher |  |
| <b>1</b> | Н                     | 1½" x 2" x 60"     | Back top stretcher   |  |
| 01       |                       | 1½" x 4¾" x 2¼"    | Slat support block   |  |
| □ 24     | 1                     | %" x 1¼" x 61"     | Seat slats           |  |
|          |                       |                    |                      |  |



**Photo 6** The arm and arm support are attached using ½" dowels.



**Photo 7** After the ½" x ½" rabbet is routed into the two ends, the start and stop points must be squared using a chisel.



**Photo 8** A %" roundover bit is used to soften the edges of the end pieces.

Photo 9 A doweling jig and drill is used to end-bore the holes in the stretchers and the center seat support.




Photo 10 A set of 1/2" dowel centers are used to transfer hole locations from the dowel pockets in the swing ends.



Photo 11 The center seat support is glued and clamped between the front and rear seat stretchers.

tom of the rear stretcher. Place the dowel centers in the dowel holes and press into place on the front stretcher. Since we're using poplar, pressing should be enough to mark the drilling location. Drill the dowel holes and test the match. Repeat the process for the rear stretcher.

Continue to locate and drill the rest of the dowel holes, then dry fit the entire frame assembly. When satisfied, finish sand all the pieces to 120 grit.

You're now ready to glue and clamp the center seat support between the front and rear seat stretchers (Photo 11). Glue first one end, then the other to the frame assembly (Photo 12).

While the frame dries, head back to the saw and cut the seat slats if you haven't already done so. Each slat should be cut to fit between the rabbets on the frame with very little side to side play. Run an 1/8" chamfer on all four top edges. Pay attention to the quality of each slat and choose the best side to face up.

After removing the clamps from the frame, drill, countersink and screw the slat support block to the front stretcher at the center point. The next step is to fill any cracks or holes on the piece and sand to the desired finish grit. We next painted all the pieces with a primer coat using an HVLP sprayer with a latex primer/sealer.

For the color coat we decided to spray the slats while loose, which makes it easier to cover all surfaces. Once the slats are painted they are attached to the frame using a ¼" spacer to assure regular spacing. We pre-drilled the nail holes to avoid splitting at the ends of the slats (Photo 13). The next step is to attach the arms to the sides. Use a ¾" x 3" eye bolt through the center of the lower arm assembly and into the end (Photo 14). The rear of the arm is attached 1" in from the back edge by screwing from the inside of the end using a 21/2" flat head wood screw.

### **Duplicating With Templates** 3 Methods to Get the Job Done In Your Shop

There are a number of methods used to duplicate shapes matched to a template. To produce the curved parts called out in our porch swing, we've chosen three different methods to illustrate; using a shaper, a router, or simply bandsawing and sanding.

A SHAPER equipped with a straight knife set flush in a ball bearing rub collar (Photo A) produces the smoothest cut.

After making the template (I like to use 1/2" 9-ply birch) trace the shape on the blank to be duplicated. Next bandsaw the blank to within 1/8" of the line. Tack or screw the template to the part. Set the shaper spindle so the top of the knife is a fraction above the work and the rub collar contacts the template. Aside from the standard safety precautions of shaper operations, be very careful in starting the cut. You must do



Photo A The straight knife set flush in a ball bearing rub collar is shown in use on the shaper. Note hand position behind work.



Photo B Using a bottom mounted bearing flush cutting bit in a router to make the second pass on the surface. A bit with a top mounted bearing was run first.



Photo C After bandsawing to the line traced from the tempiate, a spindie sander cleansup the kerf marks from sawing the shape of the arm support.



Photo D The two seat ends are shown clamped together while a random orbit sander does final sanding on the two pieces.



Photo 12 The frame is glued and clamped.

Now that all the pieces are attached the final color coat of paint can be applied. You will want to tape over the eye bolts to avoid painting the hardware. To help preserve the finish, we gave the swing a final coat of clear, water based polyurethane lacquer suitable for outdoor use.

To hang the swing we used ordinary chain that was plated to resist rust (Photo 15). You'll want to adjust the angles and chain lengths to suit your personal preference. Generally, though, the seat should be high enough so that your feet don't drag, but low enough to push off on your toes. Now sit back, throw a blanket over your lap, and enjoy the harvest moon rising. PW

Steve Shanesy is editor of Popular Woodworking and David Thiel is associate editor.

this very slowly. It is strongly recommended you also use a fence or other fixed bearing surface to act as a pivot point in easing the work into the knife. Once the template has made contact with the rub collar, continue feeding the work slowly. Always make sure your hands are on the opposite side of the workpiece and well away from the knives.

The second method uses a ROUTER and a 1/2" flush-cutting pilot bearing bit (Photo B). As with the shaper, bandsaw to within 1/8" of the template line. This method requires two bits, one with a bearing mounted on top and another bottom mounted bearing. Use the top mounted bearing bit first with the bearing running against the template. Then remove the template, change to the bottom mounted bit and run that bearing on the duplicated surface produced with the first cut. A bit of sanding will be required to even out the two passes, but this method produces accurate results.

A third option uses a BANDSAW with the kerf marks cleaned up with a SPINDLE SANDER (Photo C). Bandsaw the shape leaving only the template pencil line, but don't go inside the line. Sand to smooth out the saw marks. Use a random orbit or palm sander for final sanding. This method produces the least accurate, but acceptable results (Photo D).

#### WOOD'WORDS (wood'wurds) n.

Pinch dogs: A simple steel tool with pointed, wedge shaped ends which, when hammered into pieces across a joint, pull them together. Used in place of a clamp.

Pilot bearing: A bearing mounted to the shank of a router bit to serve as a guide to the knife thereby controlling the cut.

**Dowel Centers**: Metal inserts available in multiple sizes with a centered point on one side. The opposite side fits into drilled dowel pockets and the pointed side presses into the opposing piece locating the mating dowel pocket.

HVLP: High Volume Low Pressure spray finish system. Sprays a high volume of finish material at low air pressure. By reducing air pressure, overspray is significantly reduced. An HVLP sprayer and water based finishes can eliminate the need for a sophisticated spray booth so long as adequate ventilation is supplied. Always follow manufacturers directions and local building codes.



Photo 13 The slats are nailed into place with a 1/4" space between each piece. One or two nails may be used depending on personal preference.




Photo 14 The eye hook in place at the bottom center of the arm support.

Photo 15 This side view shows all hardware and chain in place. The swing is ready to hang.



# Bent-Wood CD Rack

Here's a scrap-box project that'll keep your compact disks handy — and refine your dry-form bending technique.

#### **By Bruce Woods**

t may be the big, dramatic projects that furnish our daydreams—the chests-of-drawers, inlaid cabinets, graceful-legged tables—but these marathon building jobs draw heavily on two resources that many of us have in scant supply: expensive hardwoods and shop time. As a result, most of us are eager for some immediate gratification, in the form of a practical project that won't consume inordinate amounts of either hours or wood. This CD rack fills the bill.

Since the dimensions of the project are all interdependent, it's best to begin with a full-size plan, which we've provided for you in the PullOut™ Plans on page 33.

Bruce Woods is editorial director of Popular Woodworking.

Begin by making a form upon which your shelfstock can be bent and clamped. To do so, use a radiuscuttina router iia to duplicate each of the two shelf arcs (see full-size

drawings on the PullOut™ Plans) onto inexpensive particle board. Cut out three of each, as seen in the photo, and tack each group of three around sandwiched blocks of scrap.

Next, cut the shelf material into pieces slightly longer and wider than the finished shelves will be; you'll need three pieces per shelf (we used some 1/4" hard board we had around; tempered hardboard or 1/4" plywood would also work, and would certainly take paint better than did the thirsty material we chose). Brush glue onto the mating shelf surfaces, and move to the form.





Use blocks to help spread the pressure of the clamps evenly. To clamp the outer edges, use blocks that are angled on one side, or cut notches into the tops of the blocks to catch the clamps. You should see the glue squeeze out, as shown. This should be wiped off with water after the clamps are in place.



Don't skimp on clamps, the more the better for this sort of job. Allow the clamped fiberboard to sit overnight before removing it from the forms.

If you're shy of clamps, but long on scrap material, you can make a concave form that will mate with the lower form, and apply even pressure across the shelf with only four clamps.



While waiting for the shelves to dry, go ahead and cut the maple sides to size, matching the angles (see PullOut plans) along the top and bottom. Use a router and roundover bit to add a little interest to the outer edges of the two sides.



Now, using a clamped straight edge, route the ¼" wide by ¼" deep dados that will later accept the ends of the two shelves. It's imperative that, during the design process, you plan the angles and curves in such away that the shelf ends enter the dados at an approximately 90° angle. You can do this by using the same radius point for all of the arcs.



Guing the same router jig setup used for the forms and a ¼" straight router bit, mark and cut, to a depth of a ¾" to ¾", the outer edges of the two curved back rails. Leaving them, at this stage, as simply two sets of curved, parallel grooves in the maple board.



Set your table saw to the appropriate cut (the fence setting will depend upon the thickness of your material; you want to leave a '4" thick rail), and (gingerly!), using multiple cuts and raising the blade about an inch at a time, slice the two curved backstops free of their board. Another, even simpler, method would be to start with '4" stock. Draw the arcs, cut them out on a band saw, and sand the edges smooth.



Now set your fence and cut the shelves to their final width. Once this is done, paint the shelves with several coats (depending on the density of your hardboard, this could be three or 23!) of gloss black lacquer.




You'll find that a piece of falloff from the Step Seven makes for an ideal support to hold the shelves in position while you cut them to the correct length (be sure to take the '4" dadoes into account when calculating the length; use the full-sized PullOut Plans to determine these lengths).



Rabbet the ends of the shelves to match the 'A" dados by carefully removing material from the undersides of the shelves, leaving a 'A- X 'A" tongue.



10 Use a rasp to ease (slightly!) the edges and nip the corners of the shelves to help them start into the pre-cut dados.





You can use whatever finish you prefer (oil finishes are lovely on maple, and bring out the glow of the wood). We sprayed two clear coats of water-base lacquer over both the maple and the pre-painted, black shelves. A quick clean-up with 360 grit sanding paper produced a glassy-smooth surface option; and a decorative home for wayward compact discs!

# Beading on a Spindle

Which came first, the spindle or the egg? It's up to you!



By Tobias Kaye

hen I first tried spindle turning I realized that I had no idea what shape I wanted to make. Bowl turning is easy — put a convex curve on the outside and a concave curve on the inside. Every subsequent bowl is merely a refinement of the same principle.

"We should learn to cut the wood as the wood likes to be cut."

Spindle turning seemed different. In retrospect I could say that my first piece had some thicker and some thinner sections and that every spindle since has been a refinement of that design. There are, however, a few principle shapes that help us to make the transitions from thick to thin and back again. The most fundamental of the thick shapes is the bead.

#### **Turning the Bead**

Forming satisfactory bead shapes is perhaps the most complex single turning operation. If a bead is to have a smooth finish and not be merely scraped to shape, the tool must execute a complex combination of roll, swing and lift movements. This is so the bevel and the cutting edge remain in the correct relationship with the surface being

cut. Unless this movement is right the result is either a poor bead shape or a catch, where the tool kicks back, cutting a deep spiral into the intended bead.

You may ask if it's worth the effort and frustration of learning this complex technique when scraping can form a lovely shape and when various bead forming tools are available.

The answer for me lies in the guiding principle of lathe work, as stated by Frank Pain, the father of modern wood turning, in his book *The Practical Woodtumer*. "We should learn to cut the wood as the wood likes to be cut," Pain says. Following this advice makes work go faster and teaches sensitivity for the wood that, in turn, makes turning more enjoyable. It also lets you bring out the best when making single pieces.

A further benefit is that the closer you get to this goal, the better the finish you get from the tool. Consequently, you'll sand less, and we all agree sanding is the least pleasant of wood turning activities.

#### The Hard Way—Skew Chisels

The best yet most difficult way to form a bead is with the

#### FOURTEEN STEPS TO AN EGG...





1 It's best to turn the egg in a chuck, so work a stub at one end between centers first, using a parting and beading tool, for the chuck.



With the log reversed on the chuck you can rough it out with or without the tailstock.

Tobias uses a skew, but you may prefer a gouge.

Locate the skew on its bevel at the cut

cutting edge of a skew chisel. When correctly done this leaves a finish second to none that requires no sanding at all. Sharpen the tool on a grinder with a large steady angle guide. The bevel produced must be even on both sides, and of a constant angle without ridges. The included angle between the two bevels should be between 35° and 45°. The tip is skewed 15° from square. A curve across

this edge makes the tool easier to handle but less precise. The curvature I prefer is about 1¾" radius. Remember that the point of cut must remain below the halfway mark of the blade, so cut with the lower half of the blade.

First mark out the size of the bead to be cut with "V" cuts using the long comer of the tool or with plunge cuts using a parting tool.


TIP
To find out at what angle the tool is ground, line the back of it up with a straight pencil line on a piece of paper or other smooth surface. Hold a straight edge against the bevel and draw a line along it. Measure the angle between the two lines with a protractor.

made identifying the top of the bead. With the handle trailing by about 15°, draw back to engage the edge. Begin the cut by swinging the handle out to 30° and then begin to roll the tool. This curves the edge down into the wood so lift the handle to follow it. As you lift the handle move it in a curve up and away from the

bead's crown, ending up nearly 20° away from the bead. In this way the handle travels in a half-moon arc.


The first swing provides a fully rounded top to the bead. If you begin the roll and lift without the swing you will likely get "gothic arch," or pointed, top beads. The last movement of the handle to 20° is necessary only if the bead stands proud of

a flat surface or meets a shoulder. Without this step such a bead would come down to the flat at an angle, not perpendicular, and would look sloppy. The tool comes around to the perpendicular, and no further, where a bead meets another curve or a pummel — because the pummel or curve prohibits any more swing-so that the junction between the two features is symmetrical. The angle of this junction should be the same as the combined angle of the skew angles.



#### **Parting Tool Beading**

The next most popular tool for beading is the parting tool. Special square section beading



**3** Yew is a dream to turn, with the shavings flowing off in a multi-colored stream as you break through the bark, sapwood and heart.



4 Use the rolling, swinging action to shape the egg (which is only an enlarged bead), bringing the handle up as you near the center.



5When working at the end of the blank it certainly helps to have the tailstock up, to keep vibration to a minimum.

and parting tools are available in  $\frac{1}{2}$ " and  $\frac{1}{2}$ " versions. The tool is used with the corner doing the cutting. The bedan is a single bevel version for use in a similar way.

To form a bead with one of these tools, the right hand side of a bead is cut using the right hand corner of the tool and similarly the left hand side with the left corner

The place to begin the cut is on the crown of the bead. Swing the tool 10° or 15° to ensure a nice rounded top and roll down the side lifting the handle where necessary. A variety of different size tools are

TIP
Use rounded skew chisels, which are easier to control than ordinary ones.

particularly nice for this technique. A good finish is possible, but not as good as with the a skew chisel. I find I get more satisfaction and better shavings using the skew. To my mind, using the parting tool isn't really cutting the wood as the wood likes to be cut.

#### **Fingernail Gouge**

Another popular technique is using a fingernail gouge. The size most useful for the average bead is the ¾" gouge. A fingernail tip to this gouge can be obtained by swinging the gouge as it is rolled against the grinding wheel (see Six Steps to Grinding a Fingernail Gouge). A large steady angle guide is a great help here. A well sharpened fingernail gouge will not have any straights or points on the cutting edge. A smooth elliptical curve from one side to the other and a round tip works best.

Beading with this tool is very similar to using a skew chisel. Place the bevel on the crown of the bead with the handle trailing by about 15° to 20°. Swing

#### FOUR TOOLS FOR THE SAME JOB ...

#### **SKEW**



1A Start with the skew handle trailing and below the tool rest. Notice how the skew is cutting with the lower half, and is fairly flat on the rest.



1B As you shape the bead, the handle is raised and swings towards the perpendicular as you roll the skew. Be sure you cut on the lower half of the skew.



1C Where two beads meet the angle of approach of each of them must be the same, so end the cut with the skew at right angles to the rest and the handle high.

#### **FINGERNAIL**



2A When using the fingernail gouge, start with the handle trailing by about 15°, and the tool ready to cut just to the forward side (right here) of the tip.



2B You'll probably find it easier to take more material off with the gouge, swinging it up and across as you roll it onto its side.



2C To account for the bevel on the fingernail gouge you will have to swing it way past the perpendicular to make the bead join a flat surface at right angles.



GUse a parting tool to mark off the other end of the egg. Don't go too deep as you'll weaken the piece before all the shaping is done.



**7**Revert to the skew for beading. Keep your hands in the same position, but swing the handle into the body as you roll and lift.



With both ends roughly shaped, turn the tailstock end down further to produce a small stub, which can be removed.

#### **PARTING TOOL**



3A The parting tool is one of the more popular turning tools for beading, and probably the easiest to use. Start with the handle trailing, and cut with the point.



3B Roll and swing the parting tool, raising the handle as you shape the bead. This produces a rough edge, which may not be the kindest way to cut wood.



3C By the time you have finished the bead, the parting tool handle will be high and the tool on its side. The junction of beads has to account for the bevel angles.

#### **BEADING & PARTING TOOL**



4A The beading and parting tool is square in section, and ground like a parting tool. Cut only with the corner of the edge, and not like a skew.



48 Swing the tool round and up, and roll it over. Like the parting tool, cutting with the corner means the wood is being torn rather than cut sweetly.



4C End the cut with the handle high and at right angles to the tool rest. Again, the junction with other beads is limited by the angle of the bevels.

the handle further out, then roll the tool to keep the cut a little to one side of the tip (left when cutting left, right when cutting right). Don't use the trailing side of the gouge. As the tool dips around the bead, lift the handle and swing it out across and away from the bead's crown until it stands out at about 40° to the perpendicular. In other words until the bevel is perpendicular, creating a sharp, smart bead profile.

While using this tool it's quite easy to go past the perpendicular and undercut the side of a bead so that it stands strongly out from the surface. This gives the spindle work a particularly dynamic look, quite different from the sloppy look of copy lathe tuming where each part of the design merges indistinctly into the next.

Gouge beading is a technique I use quite frequently. My gouge has a long bevel of about 33°. This gives a very sweet cut and feels to me as if the wood likes being cut this way. Because of the curvature of the gouge, a fine line, invisible to the naked eye, spirals down the bead. This is easily removed with the finest sandpaper. Apart from this the finish is as good as that obtained from a skew chisel.

One other method of turning a bead is by using a beading and parting tool. This method is explained in Fourteen Steps to an Egg.

#### Practice Beads by Turning an Egg

To practice forming beads, you could simply make rows of beads, but this is both tedious and unrewarding. Making wooden eggs is a simple exercise, during which the tool executes the same movements used in bead cutting.

Making wooden eggs is possible with the stock held between centers, but getting a fine finish on the ends is easier with chuck mounting. For my egg, I chose a branch of Yew that was still sopping wet from the

#### FOURTEEN STEPS TO AN EGG...



You may find it easiest to use the long point of the skew to take the stub right down, but without parting it off.



10 Use a fingernall gouge to remove wood from the waste to the chuck side of the egg. This gives access for parting off.



11 Having pulled back the tailstock, you can clean up the end. On a cleaning cut, use the long point — It's easier to feather in.

garden, risking the chance of a split. I put it up between centers and turned the end to the 1½" shape required for my Roy Child Masterchuck. For a contracting grip this chuck excels by pulling the wood back against the shoulder. Pressure at that point insures stability far out along the work. A small notch has to be cut in the spigot to accommodate the jaws, which are designed to pull.

Having put the work in the chuck, rough it round. You can

do this without using the tailstock. I use a skew for roughing most often because it causes less resistance than a gouge and cuts more pleasantly.

Advance the tailstock a touch to reduce vibration while cutting the curves. These curves are formed with the same swing, roll and lift process as cutting a bead.

Eggs are a subtle shape, every one is different. Most are lumpy and ridgy, if closely examined, yet whether they laid by

#### SIX STEPS TO GRINDING A FINGERNAIL GOUGE



Start with the gouge upright, flat on the tool rest, which I set at about 33° for the bevel.



2 As you roll the gouge over, swing It round, keeping the degree of roll and swing constant.



**3** By the end of the swing and roil you will be using the whole of the tool rest, so a steady, wide plate helps.




Having completed one side of the gouge, start again in the upright position and work the other way.



5 You need not change hands for grinding, but as you swing the tool, move one hand underneath the other.



6 As you swing the tool, watch for sparks spilling over the cutting edge to show it is being sharpened.



12 Whenever you use the long point, keep your action smooth, taking off the least waste possible to reduce the chance of tearing.



13 You will get the cleanest cut with the short corner of the skew to finish, but do take care; be firm without forcing it.



14 Cupping the egg in your left hand, cut the egg off with the long point of the skew, which you can control with one hand.

turkeys, chaffinches or emus, all eggs have a basic shape in common. The one shown in **Fourteen Steps to an Egg** is a penguin's egg.

Having cut the longer nose of the egg and finished it to your satisfaction, begin on the shorter, fatter curve. Once this is nearly complete you may well wish to alter the first end. Remember, however, that where much of the support has been cut away vibration becomes a problem if the short end is already cut thin.


The cutting edge near the long corner can be used when working near the center of rotation. When you get to cutting off, a gouge can be used to clear waste. Keep a large enough gap so that the bevel does

not put pressure on the egg. The smaller you are able to go before you separate the egg, the less cleaning up by hand will be necessary. What cleaning is necessary can be done with the skew that is still in your hand. Some turners leave a stub to ensure the end grain does not tear.

To complete, rub the egg's bum in sandpaper, twisting it against the abrasive held in the palm of your hand to simulate the rotational sanding you have done on the lathe. I finish with oil and wax.

**Tobias Kaye** is a professional turner who also teaches and writes about his woodworking specialty from his home in Devon, England.

ED. Note: This article originally appeared in *Good Woodworking*, a popular British woodworking magazine edited by Nick Gibbs.



#### WOOD'WORDS (wood'werds) n.

Bedan: A single bevel chisel that the French use as an alternative to the skew chisel. The sides are tapered from the top face down to the lower face, so the top is wider than the underside. The edge is straight across and not skewed.

Pummel: The area on a turning that is part square and part round where a turned section meets a square section, as on stair balusters and table legs. Crown: The top area of a

Skew Chisel: Rectangular section tool with bevels ground on either side to 40-45° of each other, with the edge is skewed at about 20°.

Parting and Beading Tool: A version of the parting tool, but of square section with a square cutting edge (sometimes known as a P and B tool).

# Chisels & Gouges

### A guide to what's new, including tips on what to use and when.

#### By Hugh Foster

hisels are called upon to do more precise work than almost any other hand tool. Most of us will buy only a couple sets of chisels over our entire woodworking careers, so it's important to make the right choices. There are three main types of chisels:

#### **Firmer Chisels**

Firmer chisels still have the original square cornered chisel shape. These are most useful for rough and heavy work, especially the cutting of housing joints and grooves where it's important to keep a 90° edge.

#### **Bevel Edge Chisels**

Bevel edge chisels, the kind we most often buy, were developed for cabinet work like dovetailing and chiseling clean cuts in acute angled corners. Just because these are the most popular and adaptable doesn't necessarily mean they're the kind we should use most often.

**Hugh Foster** is a noted woodworking writer and a contributing editor to Popular Woodworking. He lives with his wife in Manitowac, Wisconsin.

**Photo 1.** A range of chisel styles and price ranges are produced by Stanley including their series 1501 with shatterproof handles; series 5002 with blue, traditional carver style handles and the Goldenberg series.

#### **Mortise Chisels**

Mortise chisels are heavier versions of firmer chisels. Their added thickness will take hard use in chopping deep mortises where the blade is used for cutting, as well as for levering out waste wood. Further, their tapered shape prevents the chisel from jamming in the cut.

I've used enough chisels over the years to be quite certain that a good chisel must meet all of these qualifications:

- Well designed for the work it is to do.
- Offer the user a choice of handle material and grip.
- Come in blade widths and types best suited for the task.
- Well balanced with a good grip.
- Made of materials best suited for the tool.
- Hold an edge for a long time.
- Be easily resharpened when needed.
- Have a "replacement" warranty in case of a defect.

#### **Blades**

Often the only differences between a manufacturers' top and bottom chisel lines are in the length of the blade and the quality of the handle. I prefer longer blades over shorter ones, especially for fine work. Manufacturers can't really change blade

quality within a line of chisels. All their tools are made from high quality tool steel, hardened to a Rockwell rating around 60. For my purposes I devised a simple, practical test. I sharpened all the chisels on a grinder, honed them with a leather wheel and used them all repeatedly while building a summer's worth of projects. What I learned is that all the tools sampled sharpen nicely and hold a razor edge for a long time.

#### **Handles**

Handles are more subjective. Boxwood handles adorn my favorites in two of the five chisel sets considered here, and all the favorites feature wood handles of one kind or another. Woodworkers have long believed that boxwood handles are preferable to ash handles, and most would agree for reasons that are unprovable and all but ineffable that wood handles of *any* sort are preferable to plastic handles. Even so, I'm partial to the metal-capped, plastic handles in my old [and long out of production] Stanley 040's. These have been beaten for

Photo 4. Firmer chisels have thicker blades and square edges.

The beech handled Marples chisels at right have ferrules at each end for added handle strength. The Stanley plastic handle model may be struck with a hammer.

#### Firmer Chisels

Firmer chisels (*photo 4*) offer a thicker and heavier blade than a standard bevel chisel, partially due to their square edge design (often used for scraping). Sorby offers the Model 284 Registered Chisel fitted with ash handles and double steel hoops. Sorby's Model 285 Heavy Duty Registered Chisels are fitted with extra long double hooped ash handles. With an average blade length of 10½", (overall 19"), they are suitable for rugged work of all kinds.

A comparison of the 25mm Stanley Goldenberg and the Marples Registered Mortise Chisel reveals that the Stanley blade is .13" thick at the end of the bevel, while the Marples is .15". With both properly ground at 25°, the Stanley bevel is .31" long and the Marples bevel is .34" long.

The Marples can be struck with a regular nailing hammer rather than a mallet, so if you're going to use a hammer (or whatever else is handy) rather than a proper mallet, this is the tool for you. Marples Registered Mortise chisels remain my choice. Like any of the chisels in this class, they're a bit costly but they'll last forever.



#### **Bevel Edge**

Most of us who have but one set of chisels choose a bevel edge style. These are the most popular, if not the most useful shape.

The panel (a group of follow woodworkers who helped me test various chisels in preparing this article) unanimously selected the same tool as the favorite in the deluxe bevel-edge category: The Nooitgedagt long-blade, double hooped, woodhandled, bevel-edged chisels model #1112.95.

Samples of the Sorby Model 510s featuring Boxwood handles fitted with tapered brass ferrule, and the Marples bevel edge or firmer chisels with this handle were not part of our testing. Had they been included in the survey, I believe they

would have tied for first prize.

In 1993, when I realized I was wearing out my Stanley 040s, the 5001 series was new. I doubted they would be comparable, but I was proven wrong. The 5001s feature shatterproof handles, high quality steel with polished, lacquered blades ground at 25° (with honing at 30-35° recommended before first use).

The Sorby equivalent is the Model 500 whose cellulose acetate butyrate handles are virtually indestructible. Handle ends are lightly textured to reduce the risk of foul hammer blows. Sorby's guarantee against breakage is standard among the quality tools.

There was a three-way tie for third. Stanley 5002 blades are precision ground with blue traditional carver shape handles made from a durable polymer. Are they a step down? They're less expensive and fancy, but they're plenty nice! When I compare the Marples M444 "Blue Chip" series with the Stanley 5002, I find more similarities than differences. Both are made in England, and boast Sheffield forged



Photo 5. Choose bevel edge chisels when cutting in corners of less than 90°. Above, Robert Sorby brand chisels offer a range of handle styles in bevel edge chisels.



Photo 2. Mortising chisels from Nooitgedagt (left), Marples (center) and Goldenberg (right).

> annealed, slowly bringing it up to a consistent Rockwell rating of 60.5. Next it is polished and ground to a .0006 metallurgical finish. In the final step the blade is sealed with a polyurethane finish.

rated from its blank with one whack. Then the blade is

#### **Mortise Chisels**

I tested mortise chisels from Marples, Nooitgedagt, Sorby and Stanley Goldenberg and found all very acceptable. There's little difference between Marples and Goldenberg except that you can beat the Marples tool with a hammer, while a mallet must by used with the Goldenberg (photo 2).

I like the oval shape and plastic handle strikeability of the Marples, but at .59" thick at the shank, the Nooitgedagt is .13" (more than 28%) thicker, providing greater strength.

Sorby makes a wide variety of useful mortise chisels. Model 288 is a Heavy Duty Sash Mortise chisel fitted with an extra large diameter and double hooped ash handle. These chisels are suitable for deep mortising which demands the ultimate blade strength. Some woodworkers will prefer the Model 331 London Pattern Sash Mortise Chisel for their boxwood handles, but the Model 332 Plastic Handled Sash Mortise chisel might be more practical, as it is fitted with a cellulose acetate butyrate splitproof handle.

Despite all these good choices, it seems to me that Stanley-Goldenberg mortise chisels might well be the best choice. They now come in 8 sizes from 3-15mm. I have a 2mm Goldenberg, bought in the '70s, whose blade is so narrow that an off-center mallet blow might flex or even bend it. The current models have comfortable oval handles which I find superior in comfort to the handles on the other mortise chisels. The tools are heavy duty-great for beating and levering. I'm upgrading my chisels to the new Goldenberg version in all eight sizes!

decades in the process of cutting hand dovetails, with no signs of complaint.

A friend told me about a set of "economy grade" Stanley chisels he received as a gift. He was surprised at how flat and workable they were, and yet not so costly that you'd be afraid to use them on tasks that might harm the tool. He reports that because these chisels were so inexpensive, they've had adventures others wouldn't even dream about. When a Stanley chisel this good costs only \$5, he says, what's the problem if we occasionally do some rough work with it, such as the blade occasionally hitting some cement? While we're mainly considering more expensive tools, his thought is one that really haunts the rest of this article.

When you see the process of making a chisel, it's amazing that they're as inexpensive as they are. Photo 3 shows an interesting layout supplied by Nooitgedagt illustrating the steps which all manufacturers follow in making chisels.

They start with a steel rod of high vanadium/chromium content. The rod is forged, heated to 1100°C, then hydraulically pounded under 240 tons of pressure. The piece is then sepa-

Photo 3. From cold-rolled steel round stock to finished chisel blade, the photo at right illustrates five major steps in working the metal. In the beginning, a length of steel rod (1) with high vanadium/ chromium content is forge heated to 1100° C. The material is then pounded under 240 tons of hydraulic pressure forming a blank (2). After the rough shape is separated from the blank (3 and 4), tempering continues by slowly cooling the metal until a Rockwell rating of 60.5 is achieved. The blade is then polished (5) before finally grinding to a .0006 metallurgical finish and given a polyurethane seal (6).



Photo courtesy of Nooitgedagt



high carbon steel for longer life. Examining the %" equivalents, I see that the Stanley is 12mm, and the Marples is 13mm. The Marples is approximately %" longer than the Stanley which has "carving tool round" handles. The Marples is a squared-off round. Their circumferences are identical—3%" (which produces a working diameter of about 30mm, just shy of 1%").

Right out of the package the Marples seemed more comfortable; fifty mallet strokes into a set of dovetails, it was a tossup. I'm not sure I'd declare the handle better— just a bit different. Sorby offers comparable chisels in their Gilt Edge line. Their Model 505s offer gray polypropylene handles which are essentially similar to the Stanley and Marples blue chisels.

Bevel edged chisels permit accurate cutting in corners of less than 90°. Sorby Model 166 chisels feature Boxwood carving handles fitted with a leather washer. Their Model 167 chisels feature double hoops in solid brass for extra handle strength. The Sorbys are available in eight standard sizes from %" through 1½". Sorby models 166 and 167 are available in a 2" size as well. Sorby chisels feature blades that are individually tested for hardness, and forged from special alloy steels for longer edge retention; a solid 2" x ¾" diameter tang providing great strength and ultimate handle securement; cutting edges that are honed for immediate use; and a choice of six handle sizes. Lastly, all bevel edge chisels except the 2" size are fitted with a safety edge guard (photo 5).

Freud markets a very satisfactory bevel-edged chisel. The blades are manufactured by a well known fabricator, with the boxwood handles produced by another. As much as I pressed for names, none were forthcoming from Freud. The company doesn't regard these products as a "major" part of their product line, but offer them to help dealers round out product offerings. They're available in sets of 4, 6 and 8 sizes. These sets may well represent as good a bang for the buck as exists in the chisel market today.

Woodworkers who don't require a full set of chisels, or who want to start with a few and then add pieces as they need them, should consider the Stanley Goldenberg Set 0-16-420 consisting of 3 pieces, 10, 15 and 25mm (that's \%", \%" and 1"). The handle is European style, made of hornbeam, with a fer-

rule at both ends. The maker advertises that the tool is honed, ready for use—and I'll report that it's indeed sharp enough to satisfy all but the fussiest users.

#### Gouges

Gouges are used for shaping, carving and molding various surfaces. The price involved in purchasing a set of gouges may keep you from buying, but you'll notice their absence. Whether or not a full set is necessary depends on your need (photo 6).

There are two types of gouges. Out-cannel gouges, or firmer gouges, have curved blades with the cutting bevel ground on the outside of the curve (*photo 7*). These are used for hollowing and cutting recesses for finger grips in all kinds of cabinet work (like finger pulls in drawers) and for roughing out hand-cut bowls and other sculpted work.

In-cannel gouges, also called scribing or paring gouges, are ground with the bevel on the inside, making them one of the most difficult tools to sharpen. These are used for vertical paring of curves, cutting moldings, channeling and other curved paring work.

Of the two types, I use the out-cannel tools far more frequently, though I use only a couple of sizes on a regular basis. I use the in-cannel tools less often, but due to the detail work they are designed to perform, having the right size is almost imperative. Because of that, if finances only allow one complete set, it would indeed be a set of the in-cannel tools.

In-cannel gouges are for paring work, so you really have no reason to be hitting this type of chisel. To my hands, Marple's boxwood handled gouges are superior.

Sorby is a close equivalent to the Marples with boxwood handles that are absolutely without peer. I ranked the Goldenbergs lower than the Nooitgedagts because they seem a bit lighter and not as well finished.

If we take reasonably good care of them, chisels are a multigenerational purchase. Buy quality and comfort, and then use, but don't abuse, the tools. Lastly, whichever chisels or gouges you choose, you're almost certain to prefer a matched set over mix and match.

# Mistakes of the Hand and Mind

Arrgh! Another stupid mistake.

Don't worry — try these handy tips

and start nipping costly errors in the bud!


One of my current projects is a book with the working title Woodworking Mistakes and Solutions. The job has opened a can of worms—or termites, as the case may be. I've run across statements like, "Expertise in woodworking is gained through trial and error" and "Becoming a good woodworker is a matter of learning from mistakes." Granted, there is a human error factor, but your accepting the inevitability of error may be the biggest mistake of all.

While "playing" can be an enjoyable aspect of woodworking, step-by-step experimentation through a project can waste a lot of time — and material. My thought, though not an original one, is that we gain knowledge by going to

school. In essence, going to school means we learn from the mistakes of others so we can avoid those errors. I see nothing wrong with our stating proudly, "I taught myself," but we shouldn't be overcome by it. If we had to learn everything on our own we'd probably still be counting on our fingers.


I received a letter from a 75-year-young lady, recently widowed, who thought that woodworking would help her through a bad period and beyond. "I was so frustrated," she wrote, "and then, thank goodness, I found one of your books in a local library. If I'd had to learn on my own I would have quit before putting up my first shelf."


I see two phases of woodworking:





engineering, which deals with cutting and joining; and creativity, which deals with design and appearance, to which we react subjectively. We can design from scratch or work from plans offered by others, making changes that please our own senses. In engineering, there is rarely room for compromise. You can't stretch a board that's cut too short or widen one ripped too narrow. There are acceptable variables with many joints but it's essential that components mate precisely.

Mistakes of the mind occur when we neglect to give woodworking proper









"I see nothing wrong with our stating proudly, 
'I taught myself,' but we shouldn't be overcome by it. If we had to learn everything on our own we'd probably still be counting on our fingers."

attention. One of my recent projects was a small storage box I wanted for storing CD-ROM cases. The cases were to slide in grooves cut into opposite sides of the storage box. All went well through the material sizing and dadoing stages. I did the assembly and set the project aside to allow the glue to set. I even got to doing final sanding before I became aware of the goof that's shown in *figure 1*. Always do dry runs before the final step.


I've wondered more times than I care to admit why a board seems shorter, or, say, narrower than my measurements intended them to be. Being preoccupied may cause you to overlook important details—remember, saw blades have a "right" and a "wrong" side (figure 2). Unless you make sure the cut is on the waste side of the dimension line, you will reduce width, or length, by the gauge of the blade. This kind of mistake prompted the adage "measure twice, cut once." There's another factor to measuring twice. It slows you a bit, helping to induce a pace that's conducive to accurate and more pleasurable woodworking — like occasionally taking a deep breath.

We know how important it is for tool components to be in alignment, but we do it once and then forget that there are factors, like vibration, that can thwart us. It would be excessive to check daily, but there are ways to prove accuracy as you go. For example, when cross-cutting on a table saw, flip the cutoff and butt it against the part from which it was cut (figure 3). If they don't match, check the miter gauge. This test will also alert you when the angle between the blade and table is not 90°. The thought also applies when sawing 45° miters. You'll know attention to alignment is required if the flipped cutoff and the parent piece do not form a 90° corner (figure 4). Like many of us, I do a lot of measuring with a flex tape, but I don't always trust the hook, regardless of whether it swivels or slides. When I need to be more careful I

measure from the 1" mark (and remember to add the inch so my work won't be shorter than I intend). I mark an inverted "V" instead of scratching a dimension point. This makes it easier, for example, to place a square accurately (figure 5). When using a steel rule it's a good idea to hold it at an angle and slide the marker down a graduation line, which is more accurate than placing the rule flat and scratching a line (figure 6).


Often, when sawing a board to length, we mark the length "in the field" to be sure the board will have square ends. A better method is to square one end first then measure for length. This will reduce your chances of measuring and sawing errors (figure 7).

I've come to accept, as we all should, that lumber and plywood thicknesses have plus-or-minus tolerances. This becomes apparent, and frustrating, when you've cut a groove with a dado assembly and discover that the insert piece is too thick or too thin to fit cor-




"While 'playing' can be an enjoyable aspect of wood-working, step-by-step experimentation through a project can waste a lot of time — and material."

rectly. We can't fatten or put the material on a diet, so we compensate by using shims of various gauges. To avoid having to make frequent test cuts, I have a dado gauge like the one shown in *figure 8*. Each time I'm sure of the cut, I make one in the gauge and mark it to list the blades, chippers and shims that are needed. It saves a lot of time, eliminates



trial and error, and certainly contributes to accuracy.

If we work carefully, with full attention to the job at hand, we adopt methods that contribute to expertise while minimizing if not eliminating errors. These practices should be part and parcel of our everyday life in the wood shop.



R. J. (Cris) De Cristoforo, is a woodworking and tool authority and is a Contributing Editor to Popular Woodworking.

| ☐ YES! I want to join Woodworker's Bo<br>I have read the Membership P<br>understand I have NO OBLIGA<br>buy any more books. Please s                 | lan and<br>TION to |
|--|--------------------|
| The Stanley Book of Woodworking (#70264)   | \$ FREE            |
|  | \$ FREE            |
| with my third selection book #   | <u>\$ 12.95</u>    |
| plus my <b>FREE</b><br>12 Professional Finishing Secrets #80174  | \$ FREE            |
| add postage & handling costs   | \$ 5.61            |
| All for the amazingly low price of (total)   | \$ 18.56           |
| Club, P.O. Box 12171, Cincinnati, OH 45212-0: residents add 71¢ tax. Canadians add \$1.30 GS MC Orders call toll-free 1-800-937-0963 9AM-5 weekdays. | ST.) VISA/         |
| ☐ Check enclosed \$ (or)   |                    |
| Charge my ☐ Visa ☐ MasterCard Exp. Date  | ·—-                |
| ACCOUNT #  |                    |
| SIGNATURE  |                    |
| NAME   |                    |
| ADDRESS  |                    |
| CITY STATE   | ZIP                |
|  | LAPO               |

| <b>BOOST YOUR PROFITS</b>  |
|----------------------------|
| with classified ads in     |
| Popular Woodworking!       |
| For more information       |
| on how                     |
| Popular Woodworking        |
| will get you results, call |
| Cathy Roll today at        |
| 800/283/0963 X 3I5.        |

| ORDER FORM  ☐ Yes! Start my subscription to Popular Woodworking now at a savings of 40% off the newsstand rate. I pay just \$19.97 for 6 project-packed issues. |  |  |  |
|---|--|--|--|
| ☐ Payment enclosed. ☐ Please bill me.   |  |  |  |
| NAME<br>ADDRESS   |  |  |  |
| CITY STATE ZIP  |  |  |  |
| Mail to: Popular Woodworking<br>3300 Walnut Ave., P.O. Box 58279,<br>Boulder, CO 80323  |  |  |  |
| Add \$6 for Canadian and other foreign subscriptions.   |  |  |  |

#### **ADVERTISING GUIDE** Al-Len Pattern Co. 14 Arrow Fasteners 15 Betterway Books 4,20,71 Cascade Tools, Inc. 8-9 Diamond Machining Technology, Inc. 21 Fein Power Tools, Inc. 7 MLCS, Ltd. 5 **RB** Industries 20 The Roudebush Co. 21 Ryobi America Cvr 4 SteelMaster Buildings 20 Tree Talk, Inc. 8 Video College of Woodworking 3 Wagner Electronic Products Wildwood Designs 3 Woodcraft Supply Wood Mizer Products 14 Woodworker Magazine 19 Woodworker's Book Club Cvr 3

# Calendar

If your group is hosting an event and you would like other woodworkers to hear about it, please send all pertinent information (date, location, description and fees) at least four months before the opening date to: Calendar, *Popular Woodworking*, 1507 Dana Ave., Cincinnati, Ohio 45207.

#### California

California Carver's Guild 18th Annual Carving Show. September 16-17. Held at Coast High School, Cambria. 80 carvers will hold exhibitions, demonstrations and carving competitions. For more information, call (805) 434-2677.

#### **Connecticut**

Brookfield Craft Center Summer Workshops. Held at Brookfield Craft Center, Brookfield. August 5-6: Spindle Turning. August 19-24: Adirondack Guide Boats. August 21-25: All About Beads. August 26-27: Router Basics, Tool Sharpening, Millefiore Polyform Canes. For more information, call (203) 775-4526.

#### Illinois

*Illinois Valley Woodland Show.* August 26. Held at Marshall-Putnam County Fairgrounds, Rt. 29, Henry. Live demonstrations, exhibits, crafts, seminars, children's activities, food, entertainment. For more information, call (309) 364-3979.

#### Kentucky

Woodturning and Joinery Instruction. Classes are offered year-round. Topics include woodturning and joinery. For more information, call (606) 986-8083.

#### Maine

Center for Furniture Craftsmanship. Ongoing classes. Call or write for a brochure and registration information: The Center for Furniture Craftsmanship, 125 W. Meadow Rd., Rockland, 04841; (207) 594-5611.

#### Minnesota

Wood Carving School. Offers year-round classes. For more information, call (612) 927-7491, or write 3056 Excelsior Blvd., Minneapolis, 55416.

#### Montana

Good Wood Show VI. September 22-24. Held at Elks Club, Billings. Woodcarving competition. For more information, call (406) 628-7447.

#### Ohio

The Woodworking Shows' Greater Cleveland Show. I-X Center - West Hall. For more information, call (800) 826-8257.

#### **New York**

The Woodworking Shows' Syracuse Show. September 22-24. Held at ONCENTER - Hall A, 800 S. State St. Syracuse. For more information, call (800) 826-8257.

#### **North Carolina**

Country Workshops' Summer Tour. August 7-12: Carving Swedish Woodenware. August 14-19: Welsh Stick Chairs. August 27-September 2. Norwegian Lapstrake Boatbuilding. For more information, call (704) 656-2280.

#### Pennsylvania

Traditional Windsor Chair Making. Classes offered year-round in Earlville. Topics include woodturning and sharpening techniques for beginners to advanced levels. For more information, call (215) 689-4717.

The Woodworking Shows' Delaware Valley Show. Valley Forge Convention Center-Pennsylvania Hall. For more information, call (800) 826-8257.

#### Tennessee

Arrowmont School of Arts and Crafts.

July 17-August 11. Gatlinburg. One-and two-week workshops on multiple

woodturning topics. For more information, call (615) 436-5860.

#### Vermont

22st Annual Woodcarvers' Exhibit. August 19. Held at People's Academy Gymnasium, Morrisville. Wood carvers from several states will be demonstrating, displaying and offering work for sale. No admission charge. For more information, call (802) 644-5039.

#### Virginia

Woodworker's Club "Fundamentals of Woodworking." August 5-6. Two day intensive introduction to woodworking. Class provides hands-on experience with basic woodworking techniques and equipment. Students will practice new skills while building a desktop book rack. For more information, call (703) 255-1044.

#### Washington

Quilceda Carvers "Artistry In Wood." September 23-24. Evergreen State Fair Grounds, Monroe. 10th annual competition/show and sale, includes carving classes. Mailed entries accepted. For more information, call (206) 743-1425.

#### Wisconsin

Wisconsin Woodworkers Guild.
September 6: Show & Tell Techniques and Projects. Held at Red Carpet Lanes, West Allis. September 9: Fifth Annual Lumbering Workshop. Held at Jim Hallanda's Shop in Merton. For more information, call (414) 258-3132.

#### See you there!

The 1995 Woodworking, Machinery and Furniture Supply Fair, August 4-7, will be held in Anaheim, California. This year's theme, "A World of Ideas," sets the tone for one of the nation's largest showcases of new technology and new solutions for woodworkers. More than 800 exhibitors will fill

the 15-acre Anaheim Convention Center. Meet Popular Woodworking staff and celebrity woodworker Norm Abrams in the Delta booth! Participate in "The College of Woodworking Knowledge," the Industry's most comprehensive educational program. For more information, call (310) 477-8521.



# **News and Notes**

New products to announce? Send a press release and color transparency or slide to the Products Editor, *Popular Woodworking*, 1507 Dana Ave., Cincinnati, OH 45207, and we'll consider them for News and Notes.

#### **Heard It Through the Pipeline**

Tired of struggling with your old crank-style pipe clamps? The new **POWER PRESSTM Pipe Clamp** from American Tool might take the pressure off you and put it where it should be — on your work!

Power Press Clamps' design makes them easier to use than traditional pipe clamps, The clamp mounts on a standard ¾" pipe, but unlike other pipe clamps, does not require threaded pipe. Both ends are adjustable, and the jaws can be quickly and securely positioned anywhere on the pipe.



The clamp also features a "Flip Handle" that can be finger adjusted in the extended position at either end, eliminating awkward repositioning. The clamp also features an eight-pitch screw instead of the usual six-pitch design, allowing for finer adjustment and powerful pressure. The clamps may also stand freely, which may eliminate the need for a clamp stand.

Power Press clamps retail for about \$25. For more information, contact American Tool Companies, Inc., 8400 LakeView Parkway, Suite 400, Kenosha, WI 53142; (414) 947-2440. Circle #125 on Resource Directory Coupon.

#### Diamonds Are a Tool's Best Friend

The new **Diamond Mini-Sharp™** Sharpener from DMT Inc. allows you the freedom to sharpen your router bits, chisels, carving knives and other blade tools wherever you are — just reach into your pocket!

The size of a pack of chewing gum, the Mini Sharp™ can be used to keep a sharp, clean cutting edge on woodworking tools, including carbide and high speed tool steel. Plus, you can extend the life of your

router bits by sharpening the metal edges to maintain a keen edge without leaving your shop.

Used wet or dry, the Mini Sharp comes in three sharpening textures, fine, coarse and x-coarse.

The Mini-Sharp retails for about \$10. For more information, write: Diamond Machining Technology, Inc., 85 Hayes Memorial Drive, Marlborough, MA 01752; (508) 481-5944. Circle #126 on Resource Directory Coupon.



#### Let's get this straight

Say you don't have a jointer? **Joint A-billi-T<sup>TM</sup>** may just offer the solution you've been looking for!

Simply clamp your work in the Joint A-billi-T and run any router (with a suitable straight bit) along the edge. Join A-billi-T is really a giant jig that guides your router straight and true. You get a square edge every time.

Joint A-billi-T also cuts rabbets, grooves, tapers and dados. And it's portable — carry it easily to job sites or store it away when not needed to save valuable shop space. Mount it on your bench or clamp it to a portable work surface such as saw horses.

Joint A-billi-T ranges in price from \$135 for the 60" model to \$259 for the 120" model. For more information, contact Gudeman Enterprises, P.O. Box 126, Goodfield, IL 61742; (309) 965-2183. Circle #127 on Resource Directory Coupon.





#### Saw it loud? Don't be proud!

Does your saw blade seem just a tad too loud? Amana Tool Corporation wants to help you out with its new **Timberline**<sup>TM</sup> series saw blades. The blades feature a thinkerf design with very tight run tolerances and a low noise level.

Four different blades are available for general purpose cutting, cross cutting, a blade for laminates and plastics and an ATB grind for glass-smooth cut offs and mitre cutting.

Timberline blades retail for \$35 to \$50. For more information, contact Amana, 120 Carolyn Blvd., Farmingdale, NY 11735; (800) 445-0077. Circle #128 on Resource Directory Coupon.



#### Go west, woodworker!

If you want to accentuate your work with the popular southwestern look, try the new **Sundance and Southwestern Lodge** hardware lines from **The Woodworker's Store**.

The Sundance line features hand polished silverlook knobs, a cup pull and a standard pull with a backplate. The Southwestern Lodge hardware line, with an aged-look finish that's enhanced with verdigris green, includes a knob, a cup pull and a standard pull with a back plate.

The pieces range in price from \$2.25 for the knobs to \$4.25 for a cup pull. For a catalog or more information about these products and more, write The Woodworker's Store, 21801 Industrial Blvd., Rogers, MN 55374; (800) 279-4441. Circle #129 on Resource Directory Coupon.

#### **Under Pressure**

Looking for a versatile, high volume, low pressure paint sprayer? Titan, Inc. introduces the new **Impulse LP3**, which is ideal for many paint applications, from furniture finishing to sign painting.

Use the Impulse LP3 to spray a variety of coatings, including stains, lacquers, enamels, polyurethanes, finish quality latexes and multi-colored coatings.

Weighing only 20 pounds, the Impulse LP3 utilizes a high volume of low pressure

air produced by a three stage tangential turbine. This process atomizes coatings without a lot of overspray and bounceback — in fact, it offers a transfer efficiency rating of up to 90%.

The Impulse LP3 also comes with Titan's new Pro-Finish Gun and .051 Needle/nozzle set, #0 Indexing air-cap, a quart cup and and 20' of air hose with quick disconnect fitting. It retails for about \$600. For more information or a demonstration, contact Titan, 556 Commerce St., Franklin Lakes, NJ 07417, (800) 526-5326. Circle #130 on Resource Directory Coupon.



#### **Resource Directory**

#### **ABRASIVES**


econ-abrasives. Econ-Abrasives custom makes abrasive belts up to 52" wide in any size and grit. Sandpaper is our specialty; we can help you answer any questions you may have on product applications. Call now for your free catalog; it contains hundreds of abrasives and woodworking accessories, including: safety equipment, velcro<sup>®</sup>-backed discs, wood clamps, wood glue, drawer slides, hinges and much, much more! Circle #102.

#### HAND TOOL MANUFACTURERS

ARROW FASTENER COMPANY, INC. is one of the oldest American hand tool manufacturers. In addition to its world famous line of all steel staple gun tackers and staples, Arrow also produces a full line of Brute steel rule measuring tapes, rivet tools, hot melt glue guns, and supplies. Arrow . . . the standard of excellence by which all others are judged. Circle #100.

**RYOBI.** AMERICA CORP. offers a wide range of power tools, outdoor power equipment and builder's hardware for the serious do-it-yourselfer and professional tradesman. Ryobi offers a wide selection of bench-top, cordless, portable and specialty power tools; a variety of gas, electric and battery-powered outdoor power equipment; and an assortment of builder's hardware. Designed and manufactured to exacting standards of quality, durability and reliability, yet affordable. Free catalog. **Circle #106.** 

FEIN POWER TOOLS. New Triangular Sander eliminates hand sanding. Free brochure shows how you can sand, with a power tool, all those areas where before you had to fold up a piece of sandpaper and "finger sand." The Fein Sander is ideal for sanding along edges, moldings and more. Circle #103.



#### **HAND TOOLS - RETAIL**

WOODCRAFT SUPPLY CORP. offers more than 4,000 of the finest quality woodworking tools, books, supplies and cabinetry hardware in our free 154-page complete full-color catalog. Circle #112.

#### **MOISTURE METERS**

WAGNER ELECTRONIC PRODUCTS, INC. "Wood-Friendly" L606 Moisture Meter uses advanced electromagnetic wave technology to accurately measure wood moisture content from 6% to 30% to a depth of 3/4". No pins to "abuse" wood, leaving ugly holes. Check out boards from top to bottom in just seconds before you buy and avoid the headaches of splitting, warpage, delaminating and failed glue joints. Call today for your free literature. 1-800-944-7078. Circle #115.

#### **PLANS & KITS**

ACCENTS IN PINE. Huge assortment of popular shop-tested designs! More than 1,500 full-size patterns conveniently grouped into 78 jumbo blue-print sets! You get patterns plus complete instructions, sketches, material lists, decorative variations, and tips and techniques! Create hundreds of unique projects for fun or profit. Order direct from our classified ad or request our illustrated catalog plus sample pattern for only \$2. Circle #300.

BUCKBOARD BENCH KIT. Includes authentically designed steel springs that give a little. Metal arms, backrails, complete hardware & detailed instructions. 42" X 13", regular seat height. \$49.00 includes shipping (UPS). Also available, precut & drilled oak only \$60 additional. To order or for more information write: The Roudebush Co., P.O. Box 348, Star City, IN 46985. Visa/MC. 800-847-4947. Circle #108.

WILDWOOD DESIGNS. Scrollsaw Fretwork Patterns and supplies. From simple projects to 50" tall clocks. Over 300 patterns for the scrollsaw enthusiast. Clock movements, tools, books, plywood sawblades as low as \$21.95 per gross. Great ideas for the hobbyist or for profit - including clocks, frames, jewelry boxes, furniture & silhouettes. Circle # 111.

COMMON SENSE DESIGNS offers 56 boat designs, all by premier yacht designer Phil Bolger, 32 of which are designed for first time builders. If you can build a bird house, you can build one of these easy and inexpensive boats and have a better boat than you can buy. All the parts that control the shape of the boat have dimensions, making them easy to lay out without lofting. To order a catalog see our classified ad. Circle #113.

#### **SHOP ACCESSORIES**

streelmaster Buildings provides the perfect backyard woodworking shop. These amazingly strong archtype steel buildings are versatile and fire resistant. SteelMaster provides 100% open, usable interior space, and can accommodate all of your woodworking equipment easily. SteelMaster buildings still set the standard for quality in the steel building industry. Call today at 800-888-4606. Circle #107.

AL-LEN PATTERN COMPANY. Try "The Gripper"- the amazing tool that turns stubborn and hard-to-reach handles easily. This lightweight, ready-to-use tool won't slip or scratch chrome fixtures and finishes, and its universal fit is guaranteed. Send \$6.95 + \$1.50 s&h (\$8.45) to order or call 412-475-3708 for more information. Circle #301.

JOINT A-BILLI-T is just as its name implies, a tool for fool-proof glue joints. Use your router to cut these joints flaw-lessly in your shop: dadoes, rabbets, angle cuts, squaring large panels with a perfect glue joint every time. Circle #127.

#### SOFTWARE

WOODS OF THE WORLD is the first interactive, multimedia encyclopedia of the world's wood species, with woodworking characteristics, mechanical and physical properties, geo-

#### **Resource Directory**

graphical origin maps, environmental profile and full color pictures of woods and wood-based composites. For Mac or PC-Windows. WoodMatch (300 species) \$39; Pro version (900 species) \$249. Tree Talk, Inc., PO Box 426, Burlington, VT 05402. 800-858-6230 or 802-863-6789. **Circle #109.** 

#### STATIONARY POWER TOOLS

**rbi**ndustries, inc. While RB Industries goes back 60 years, this is the first time we have brought together all our precision-made tools and accessories in one catalog. The Hawk Precision Scroll Saw, 4-in-1 Woodplaner, Panel Master Door Machine, Router Mates, and more. Quality equipment built in the heart of America. When you buy from us, you deal directly with the manufacturer. Our prices, quality, and five-year warranty reflect this. Free. **Circle #105**.

#### **TOOLING - BITS & BLADES**

MLCS. Professional woodworking products. Large discounts. New expanded catalog featuring a

huge selection of carbide-tipped router bits, raised panel door sets, shaper cutters, solid carbide bits, the router speed control, plus our unique line of clamps, tools and supplies. Save 50% to 70%. Value, quality and prompt service guaranteed! Free information. Circle #104.

WOODCRAFT BANDS, INC. Our blades provide you with a savings of 30% to 50% off major brand blades. We have the 80" length in 1/8" X 7 1/2" or 15 TPI and the 1/4" x 40R6 TPI. Also, we have the professional blades from 1/16" to 3/4" in several tooth patterns. Free Catalog. Circle #114.

DIAMOND MACHINING TECHNOLOGY, INC. DMT Diamond Whetstones serve sharpening needs of consumers and commercial and industrial hand tool users. The unique diamond surface is fast, easy, clean, durable, and true. The monocrystalline diamond surface hones all hard materials, including tool steel and carbides. Four grits (220,325,600 &1200) available. Non-porous surface needs no oil - use dry or with water. Circle #126.

CASCADE TOOLS, INC.

is a leading mailorder supplier of router bits and shaper cutters. Its 64-page catalog features an incredible variety of highquality cutters and bits designed for most woodworking and milling applications. Cascade also offers a fine selection of woodworking accessories and supplies, from dust collection systems to pneumatic nailers. The catalog is free. Call 800-235-0272 to order. Circle #116.

#### **VIDEOS**

THE VIDEO COLLEGE OF WOOD-WORKING, INC. The FUNdamentals of MODERN Woodworking is a 60-minute video with accompanying workbook, plus a set of plans and planning sheets, which takes you from a basic understanding of wood, tool selection, maintenance and safe operation, through the essentials of joinery, cabinet construction and finishing. Circle #110.

# **Resource Directory**

Popular Woodworking®

#### 1507 Dana Ave. Dept. CCC Cincinnati, OH 45207

Circle numbers below corresponding to items in this issue.

| 100 | Free | 114 | Free    |
|-----|------|-----|---------|
| 102 | Free | 115 | Free    |
| 103 | Free | 116 | Free    |
| 104 | Free | 125 | Free    |
| 105 | Free | 126 | Free    |
| 106 | Free | 127 | Free    |
| 107 | Free | 128 | Free    |
| 108 | Free | 129 | Free    |
| 109 | Free | 130 | Free    |
| 110 | Free | 300 | \$2.00  |
| 111 | Free | 301 | \$8.45  |
| 112 | Free | 888 | \$19.97 |
| 113 | Free | 999 | \$26.97 |
|     |      |     |         |

To order the next six issues of

Popular Woodworking,

U.S. residents send \$19.97-circle #888 above.
Canadian residents send \$26.97-circle #999 above.

To Ensure Prompt Handling of Your Order, Follow These Instructions:

- Circle your choices.
- Enclose check or money order for cost of catalogs/items.
- Send coupon and remittance to address above.
- We will process your requests promptly. You will receive information directly from the advertiser.
- Coupon expires January 5, 1995.
- Please allow 4-6 weeks for delivery.

| Name                             |   |        |
|----------------------------------|---|--------|
| Address                          |   |        |
| City                             |   |        |
| State                            | Zip   |        |
| Orders for information           | n or subscriptions accepted only from U<br>ces must be in U.S. funds. | .S. or |
| Are you a subs<br>I am enclosing | scriber? (Check one)  |        |
|                                  | \$ TOTAL REMITTA  | ANCE   |

# Black Walnut

North America's premium hardwood for practicing the cabinetmakers' art.

Traditionally one of the most sought-after hardwoods in North America, black walnut easily lives up to its reputation. Although a little expensive, this is a wood that will earn you high praise when used in just about any project.

#### **General Description**

There are a half dozen species of walnut tree in North America, but black walnut (Juglans nigra) is by far the species most frequently sawed into lumber. The wood is also called American walnut, or sometimes American black walnut, both probably representing efforts to distinguish it from its European cousin, Juglans regia.

Compared with oaks or maples, black walnut is less common. However, the tree's range is more widespread than maple, stretching from southern Vermont westward to the Great Plains, and south to Texas and back east through the Piedmont. It is also found in Canada. The prime growing region for Black walnut is the Ohio River Valley.

Black walnut trees are fussy, thriving only in soils that are deep, well drained, rich and moist. They do not like to grow near other species and need lots of bright sun to flourish. They are found only on a spotty basis in mature forests and pure stands are rare.

The tree will grow straight with a small crown when in competition with other trees. However, since many black walnuts grow in the open, particularly at the edge of open fields, branching can start very low therefore dividing the trunk often. Burls frequently grow at unpredictable points on the trunk. Growth in general is relatively slow; these trees often require 150 years to reach a height of 80 feet. However, a

walnut tree can survive as many as 250 years, provided soil and light conditions remain constant. Its hallmark is the hard, black walnut, which is edible. The husk has been used as a source of yellow dye.

The wood of black walnut is moderately heavy, hard, stiff and often remarkably handsome. The heartwood is light brown to dark brown, with a sapwood that looks dirty cream. However, the amount of sapwood in comparison to the amount of heartwood is modest for a hardwood. The variability of walnut's grain makes it attractive. Everything fountain-like crotches and swirls to wavy fiddleback and

striped grain is possible. Walnut burls provide truly unique grain patterns, especially when veneers are expertly matched.

The stability of kiln-dried walnut is quite good, which gives it an advantage over most oaks and some maples. It rarely checks or warps when in open storage, and shows relatively little movement in finished projects. It's highly resistant to decay, even when in contact with the ground. It is shock resistant, and moderately easy to steam bend. Black walnut traditionally has been a wood



A fine example of crotch Black walnut veneer. The veneer is sliced from the tree at the intersection of a main branch to the trunk. It is typically used as the panel for door frames in cabinetwork. (Crotch veneer courtesy of Constantine's.)

used for fine finish carpentry and cabinetmaking. Architectural paneling, furniture, gunstocks, cabinets, interior finish and decoration are among its chief uses. In colonial times, it was also used for fence posts, feed troughs and tool handles.

#### **Working Properties**

In general, black walnut is easy to work, although it does have some shortcomings. Most of the difficulties seem to be confined to individual planks, not an entire load of lumber. Because black walnut trees often grow in the open, a

The flat cut or plain sliced black walnut veneer at right is arranged in a pie shape, or sunburst. Each adjacent wedge of the pie is taken in sequence from the flitch with alternate pieces flipped to bookmatch them as well. (Veneer lay-up by Bill Kraemer Veneers, New Albany, Indiana.)

lot of tension can build up in the wood. When released in the woodworking processes, this tension can bind up even the sharpest saw blades, particularly when ripping.

Tension in the wood can also result in chipping when the wood is planed. Planer chipping is also caused by internal knots and defects. Because the wood is so valuable, sawyers are reluctant to cull out boards that may contain a defect here and there but are otherwise usable. Sometimes those defects are visible, sometimes they're not. Either way, they can cause headaches for the woodworker.

Still, hand planing, power planing, routing and boring in run-of-the-mill boards cause few problems, because black walnut trees tend to grow straight-grained. Nevertheless, cross-cutting with a circular saw or hand saw can sometimes leave a rough edge that can be prevented by scoring the line before cutting.

On the other hand, sanding is a pleasure, usually because of the very good results you get in power planing. I was able to start right in with 150-grit sandpaper after running planks through my planer. You can work up rapidly to 320-grit or finer, producing a highly polished finish.

Turning walnut on a lathe also yields good results. Although not quite as tight and closed-grained as beech (PW #77) or hard maple (PW #60), walnut's good woodworking and sanding qualities make it relatively easy to turn small details and obtain a good finish. Turned shavings come off easily and evenly, and the resultant dust gives the air a smell of sweetened autumn leaves. Black walnut is also an easy wood to carve with hand or power tools.

Fastening and gluing black walnut is a snap. With screws, a correctly sized pilot



hole is advisable, but wax lubricants are unnecessary. The wood resists glue staining well, and both resin and epoxy glues present few complications.

#### Finishing

To me, finishing black walnut in anything other than a clear varnish, shellac, oil or lacquer is risky. I have seen professional wood finishers achieve interesting results by using stains on black walnut, but it seems to take a lot of finishing experience to know just the right mixtures.

If you have some experience staining wood, you'll find walnut accepts stain nicely, without the blotchiness associated with some stock such as birch, maple and pine. As long as the stain is not too dark, it can enhance the natural color. Walnut, however, can be beautiful when finished clear, with no color added.

Black walnut's grain pores may require you to use a paste grain filler. Be careful, though. It must be tinted (usually a brown) so that the filler is not visible in the pores after drying. Mix a little oil stain in an oil-based neutral filler, or buy premixed filler with the color already added.

Coloring black walnut for the best effect may take some practice. Professional finishers often choose a dye rather than a pigmented stain, because a dye generally enhances the grain patterns while a pigmented stain can mute

the wood's natural colors and grain patterns. But of course, dyes will fade in the sunlight while pigmented stains hold up much better over time. Colors are a matter of personal taste.

#### **Availability**

Black walnut is widely available throughout the United States. It's the quantity, quality and price that's the problem.

Unless you live in the heart of black walnut country, expect to pay from \$3.50 to \$9 per board foot. The wide variation in price is due to several factors, not the least of which is how much figure there is in the wood. Fiddleback, striped, crotch and burled wood all bring premium prices. There are also periodic "runs" on black walnut, when the wood suddenly becomes very stylish and is featured in national newspapers and fashion magazines. This happened most recently about ten years ago and the price of black walnut temporarily soared. And of course, the farther you live from black walnut country, the more you'll pay.

In all cases, beware of some of the tricks of the trade. Because black walnut is so desirable, some sawyers will go to questionable lengths to get the most out of those expensive logs they bought. Black walnut is often cut into 8/4 planks, although some 12/4 and 16/4 planks are available by special order. Still, these



thicker planks tend to mask several problems common to black wainut. Extra thickness will stabilize the plank more than if it were cut into 4/4 planks. Sweep, warp and twisting are therefore less common in 8/4 planks. Cut them open, though, and you may find a decided bow in what appeared to be a straight plank. Moreover, an 8/4 plank will hide defects buried inside. In this way, more sapwood and knotty wood can be sold

as a higher grade lumber. In fact, this

Black walnut burl has a distinct pattern and usually shows a wide contrast in color. (Burl veneer slice courtesy of Constantine's.)

extended to stacking larger shipments of black walnut so that the lower quality planks will be in the middle or on the bottom of the stack, hidden from easy detection.

You can sometimes keep your black walnut costs down by telling the sawyer you'll accept sapwood boards as well as heartwood. Many production cabinet shops won't accept boards with sapwood in them, leaving lumber yards to market that wood as best they can. However, I think a little sapwood mixed into a project gives it personality. Plus, it appeals to my bank account.

Another solution to the high price of black walnut is using veneers. Depending on the grade of wood, black walnut veneers cost from 50¢ to \$4.50 per square foot. You can get excellent figured veneers between 50¢ and \$1.50

per square foot, including striped and wavy figure. The higher prices are for premium burls, crotches, book-matched grain and the like. By the way, burls and crotches in veneer form are more stable, much easier to work with, and much more likely to be available in veneer than in solid lumber form. Black walnut plywood is also a way to keep costs down. It's usually readily available or can be shipped within a few days.

To sum up, working with black walnut is to a woodworker as a fine filet mignon is to a cultured gourmand. It's not always necessary but it sure is a pleasure whenever the opportunity comes along.

Ken Textor is a woodworker, writer and contributing editor to Popular Woodworking who lives in Arrowsic Island, Maine.





### The Winner of our "Caption the Cartoon Contest #12"

from the May issue and recipient of the Bosch Variable Speed Plunge Router is:

Norman Stewart from Tamwater, WA

The runners-up receive a one-year subscription to Popular Woodworking: Rick Wiles, from Westhampton Beach, NY, for:

"Five minutes ago, as a sign of the truce, Billy McCoy and Jim Hatfield had started on the project."

Mark Mahoney, from Alexandria VA, for:

"Nail guns don't shoot people's butts. People with nail guns shoot people's butts."

#### Classifieds

#### BOOKS & CATALOGS

MOUNTAIN WOODCARVER'S CATALOG. Send for your one year's subscription. P.O. Box 3485-A, Estes Park, CO 80517.

PROFESSIONAL STAINED GLASS SUPPLIES. Learn fascinating craft! Catalog \$2.00 with free bonus coupons, instruction booklet. Whittemore, Box 2065MU, Hanover, MA 02339.

GET YOUR FREE CATALOG OF NEW WOODWORKING BOOKS - From shop jigs to furniture plans, you'll find books packed with in-depth instruction, detailed illustrations - all offered at GREAT PRICES!! Write to Betterway Books, Department J, 1507 Dana Avenue, Cincinnati, OH 45207.

#### **BUSINESS OPPORTUNITIES**

your woodworking business. Grants/loans to \$500,000.00. Free recorded message: (707) 448-0270. (KC1)

**EASY WORK! EXCELLENT PAY!** Assemble products at home. Call Toll Free (800) 467-5566 X 3445.

ASSEMBLE EASY WOODCRAFTS and more at home. Nations most respected program. Guaranteed! 1-800-377-6000 ext. 7110

#### COMPUTER SOFTWARE

#### **COMPUTERIZED PATTERNWARE:**

Windows based woodworking program. Unlimited number of sizable patterns, no more tracing paper. Halloween/Thanksgiving Templates contain 6 Halloween and 4 Thanksgiving Templates/Stencils. Order Today! \$12.95, \$3.00 shipping. Check or money order. Write for free catalogue. American Software Design, P.O. Box 4379, Middletown, RI 02842. 1-800-513-6094.

#### 1000s OF WOODWORKING TIPS.

tricks, sources, opinions, Q&As. Easily search and read topics gathered from worldwide resources. Windows software. Updated monthly. Only \$9.95. Solid Oak Software: 1-800-388-2761.

#### FINISHES

## AUTHENTIC PATINA FINISHES MAY BE APPLIED TO ANY SURFACE!

Now you can create beautiful true patina finishes just like the pros. Simply apply our Green, Blue, Black, Burgundy & Rust patina solutions over our Liquid Copper coating or on natural Brass, Copper & Bronze. For more information call or write:

PATINA

1-800-995-9946

P.O. Box 70228, San Diego, CA 92167

SPRAY-ON SUEDE. LINE BOXES EASILY. Free brochure with sample, new Mini Flocker. DonJer Products, Illene Court, Bldg. 8G, Bellemead, NJ 08502; (800) 336-6537.

#### FURNITURE RESTORATION

Furniture Restoration Manual Serial Refinish Like A Professional - Tips, Tricks & Secrets, Written By A Craftsman, Manual Guaranteed, Only \$9.95.

Lomar Publishing, 218 Bridgewater Drive, Newport News, Va 23603-1439

#### MISCELLANEOUS

**VACUUM WORK TABLES.** All wood. 110V. Filters 200/1900 CFM. Custom Made Craft Shops, Labs, Industrial. Call for Details: 1-800-598-3687.

#### POST OFFICE BOX BRONZE DOORS

No. 1 \$8.00; No. 2 \$9.00; No. 3 \$10.00; plus \$1.00 each shipping. SASE to: Hubbert Woodcrafts, P.O. Box 1415, Fletcher, NC 28732; 704-687-0350.

BUILD, RESTORE, REPAIR, Refinish!
Carvings, Moldings, Brass, Hardwoods, Veneers, Upholstery, Caning, Lamps.
\$1.00 for unique wholesale catalog.
Van Dyke's, Dept. 50, Box 278,
Woonsocket, SD 57385.

CANING AND BASKETWEAVING SUPPLIES. Shaker Tape, naturals, books, tools, more! Retail. Wholesale. Catalog \$2.00. Royalwood Ltd., 517-PW Woodville Rd., Mansfield, OH 44907. 1-800-526-1630. FAX: 419-526-1618.

WHOLESALE WOOD PRODUCTS, spindles, wheels, etc., Clockworks and accessories. Howee's, Rt. 7, Box 633PW, Joplin, MO 64801.

#### **PLANS & KITS**



MAKE CARS LIKE THIS FROM

MAIL TO:
VM WOODEN TOY CARS
P. O. Box 2347
GILBERT, AZ 85299-2347

ACCENTS, Dept. MR85, Box 7387, Gonic, NH 03839

ILLUSTRATED CATALOG - \$2.00(Free with order)

#### 2000 WOODCRAFT PATTERNS.

Fun/profit. Catalog \$2.00 (refundable). E-Z Design, P.O. Box 234, Dept.C, Washington Mills, NY 13479.

**FORGET EXPENSIVE LUMBER!** Build with sawdust! GBW, POB 158, White Sulphur Springs, WV 24986.

EXCLUSIVE: CEDAR GRIST MILL planter plans. Water propelled. Attracts gardeners and nature. Wonderful and unusual. \$28.95 Ppd. Send LSASE for inquiries. Homelife Enterprises, 3005 165th Ln. N.E. Ham Lake, MN 55304.

LAWN/PATIO FURNITURE, PICNIC tables, porch swing. Catalog \$1.00. LLE, POB 908P, Cornville, AZ 86325.

**ADVANCED SCROLL SAW PATTERNS** \$1.00 for brochure 'C'.Nelson Designs P.O. Box 422, Dublin, NH 03444.

BOAT PLANS - PATTERNS - KITS - 7' to 55' - Powerboats - Rowingboats - Sailboats - Quick/simple stichenglue. 168-page DESIGN BOOK - \$5.00 (Sent AIRMAIL). Includes FREE "Boatbuilding Supplies" catalog. "EPOXY MANUAL" - \$2. GLEN-L, 9152 Rosecrans, Box 1804/PW5,

Bellflower, CA 90706-2138. Phone: 310-630-6258.

#### Classifieds

**WOODEN** Geared Clock plans. Easy, unique! FREE information. Riggs Publications - B, Box 2983, Gardnerville, NV 89410.

TWENTY BIRDHOUSE PLANS (DESIGNED 100 YEARS AGO!) Bluebirds, Martins, Songbirds, \$5.00. Woodartist, Box 31564 PW12, Charleston, SC 29417-1564.

MAKE BANDSAW TOYS from 2X4 Scraps! Earn at least 300% profit per sale! 1957 Corvette, 1957 Chevy and more FULL-SIZE patterns. Free brochure - send self-addressed, stamped envelope to: Woodcrafts, Rt. 10- Box 708, Lake City, FL 32025.

BUILD A BETTER BOAT THAN YOU CAN BUY with Common Sense Designs. The Design Book has 56 sail, power, paddle and row boats designed for the home builder, \$10.00 (book rate) \$12.00 (priority mail) - Common Sense Designs, 11765 SW Ebberts Ct, Dept. 101, Beaverton, OR 97008. Phone or fax orders (503) 524-8264.

SHAKER-STYLE CHEST OF DRAWERS. Complete plans and instructions with jigs. \$5.00 Check or MO to Holden, 30 D Street Dept. PW, Chula Vista, CA 91910-1910.

**BUILD PERFECT STAIRS!** Detailed instructions for any application, \$6.00. C. Howe, 3405 Pine Valley Drive, North Little Rock, AR 72120.

AIR HOCKEY TABLE - 3,5,7 foot. \$5.00 Ea., All 3 \$7.95. Source for paddles, puck and fan. DDH -DESIGN, Box 1181, Maple Grove, MN 55311-6181.

MAKE "ASTONISHING" BALANCING TOYS!!! Wooden "performing" animals . . . people! Thrilling results! Details . . . free!!! Send today! Pleasure Crafts, PW85, Rt2-1485, Mannford, OK 74044.

#### **VIDEO**

**SANDBLAST PHOTOS & ART INTO**Wood! Amazing new process.
Complete how-to video. 31 minutes.

\$19.95 + \$3.00 S&H. Visa/MC/Amex. Video University, 3501 Happy Hollow Rd., Dept 1P, Independence, MO 64058; 800-927-8444.

#### WOODS

# DOWELS — PLUGS — PEGS Manufacturer Direct Largest & finest selection Oak, Walnut, Hickory, Maple, Cherry, Mahogany, Teak, even treated dowels. Quantity discounts. MIDWEST DOWEL WORKS, INC. 4631 Hutchinson Road Cincinnati, OH 45248 (513) 574-8488 Catalog \$1.00

#### FACTORY SECONDS & FIRSTS!

Now you can buy either grade, depending on your needs! Huge selection of Shaker Pegs, Gallery Spindles, Wheels, Balls, Eggs, Knobs, Cargo, People, Spools, Fruit, etc. Available in both 2nd and 1st quality at low-low prices. Our promise to you - Price, Selection, Quality, Service! Catalog \$1.00. Casey's Wood Products, P.O. Box 365, Woolwich, ME 04579; 800-45-CASEY.

## **Classified Advertising Order Form**

Send to:

# Popular Woodworking®

Attn: Cathy Roll, 1507 Dana Avenue, Cincinnati, Ohio 45207 Phone: (800) 283-0963 ext.315 • Fax: (513) 531-1843

| (Please Print or type) |  |
|------------------------|--|
| Your Name              |  |
| Company (name in       | ad)  |
| Address                |  |
|                        |  |
| Phone                  | Fax  |
| Payment:               | _Check enclosed  |
|                        | _Bill my Visa/MasterCard   |
| Card No                |  |
|                        |  |
| Signature              |  |
|                        |  |
| _                      | e print or type. Use separate sheet of paper for additional word |
|                        |  |



**Classified Display** 

 1X
 3X
 6X
 12X

 1-inch @ \$300
 \$275
 \$250
 \$200

 2-inch @ \$600
 \$550
 \$500
 \$400

 Free set-up. Discounts for consecutive advertising.

Reading Notices:

15 word minimum. Save 15% with 3 issues.


15% Discount with 3 Consecutive Issues:

Frequency discounts apply in combination with Popular Woodworking. Contact Cathy Roll for details.

#### Classifieds

**BALTIC BIRCH PLYWOOD** - For scrollsawing - catalog, coupon and sample kit - Send \$2.00 to Duckwork's Woodcrafts, Dept. PW, 7736 Ranchview Lane, Maple Grove, MN 55311.

FREE SYCAMORE SAMPLE (plus \$2.65 shipping and handling, refundable with first order). SYCAMORE (only available quarter sawn), WALNUT, RED OAK, WHITE OAK, RED CEDAR, OSAGE ORANGE. Band sawn, kiln dried. Small orders welcome. Evening Shade Exotics, HCR 60 Box 46, Evening Shade, AR 72532-9513. Phone: Randy or Bobbie, 501-266-3662.



### **Get Your FREE Catalog of Woodworking Books!**

Get your FREE catalog packed with informative books for woodworkers. Just look at what you'll find:

- Sooks to Save You Time and Money including a complete mail order guide for everything from plans to paints.
- The Best Advice on Finishing from picking the perfect finish, to maintaining and repairing its luster.
- Step-By-Step Furniture Building Guides including fully-illustrated plans and detailed price lists.
- Inventive Ideas for Selling Your Work to help pay for shop improvements or generate a little extra income.
- Plus a Great Selection of do-it-vourself books and much more!

### To order just call TOLL-FREE 1-800-289-0963

and ask for Department G or write to

Betterway Books, Department G, 1507 Dana Avenue, Cincinnati, OH 45207

### **Build Your House Right!**



The Complete Guide to Contracting Your Home, 2nd Edition

Learn the key steps in getting your home built and where you can save money! This book covers it all, from financing and site selection to working with "subs" and

building inspectors. You'll get all the information and "how-to's" you need whether you watch from a distance or roll up your sleeves and manage the project! #70025/\$18.99/288 pages/paperback

| YES! Please send me            | copy(ies) of The            |
|--------------------------------|-----------------------------|
| Complete Guide to Contra       | cting Your Home, 2nd        |
| Edition (#70025), for \$18.5   | 99 each. Add \$3.50         |
| postage and handling. Ohio res | sidents add 5.5% sales tax. |
| Allow 30 days for delivery.    |                             |
| VISA/MASTERCAR                 | D ORDERS CALL               |

### TOLL-FREE 1-800-289-0963

| □ Payment enclosed \$                             | (or)                         |
|---|------------------------------|
| Charge my 🗌 Visa 🔲 MasterC                        | ard Exp.Date                 |
| Acct. #   |                              |
| Signature   |                              |
| Name  |                              |
| Address   |                              |
| City  |                              |
| State   | Zip                          |
| Send to: Betterway Books<br>1507 Dana Avenue • Ci | 3192<br>ncinnati, Ohio 45207 |

### Out of the Woodwork

continued from p. 72

yearn for what I had not. When it came to furniture, home improvements, the new deck or built in appliances, all hinged on whether or not we could get published.

When we moved to California from New York after having sold most of our worldly goods, the kids slept on the floor for months until an editor approved our proposal for a story on how to build bunk beds.

Once, when coffee table projects were hotter than espresso at Starbuck's, we had six flawless models crowding our sofa-less living room. Half a dozen editors were eager for coffee table how-to's. The overflow, except for one unit, went to the first visitors who arrived after acceptance of the stories. This left us with a red-lacquered Oriental design that was quite handsome but not in keeping with our rustic lifestyle.

At that time, door-to-door solicitors had not yet been discouraged in our friendly town. One day, a former usedcar salesman, who had turned his mar-

keting skills to Eureka vacuum cleaners, showed up at our door. Since we were making do with a Bissell sweeper and an electric broom, the complete ensemble of cleaning tools put an avid gleam in my eye.

Cris listened politely, professed interest, asked questions, and ended up persuading the seller to swap a fullyequipped Eureka for the red-lacquered table. To this day I chuckle to think of the man who considered himself a hotshot salesperson as he drove away with a table straddling the back seat of his car while we took turns trying out our new accessorized vacuum.

When Cris was producing a book on concrete and masonry, I pitched in to help with the bricklaying and concrete mixing. This did more for my chest than Madonna-inspired Unfortunately, my shoulders and biceps developed as well. It took some time before I lost the linebacker look.

A how-to writer's wife teaches her patience, resilience, tolerance for sawdust, flexibility and resignation. Still, if you don't mind waiting for money while you ponder which bills to pay on schedule, if you can cope with unpredictability as you receive enough rejection slips to paper a room, if you can relinquish fringe benefits and stock options, and if you can face the discipline and isolation of working alone, go do it! The freedom of being your own boss with just a five second commute to work may compensate for everything else.

Once your friends, family and perhaps even you have accepted the fact that you might be tinged with madness to live this way, the rest is a piece of cake ... or plywood!

Woodworking, sawdust, hand and power tools are the hubs around which the wheels of our life revolves.

And it's a wonderful life.

Mary Cristy, a newspaper columnist and freelance writer, is married to Popular Woodworking Contributing Editor R. J. (Cris) De Cristoforo.

# Married ... with Craftsman

An idyllic life blessed with everything ... except a regular paycheck.

Life with a do-it-yourself writer is a kaleidoscope, a merry-go-round, a "chicken tonight, feathers tomorrow" romp, with mood swings that range from jubilation to desperation.

No marooned sailor on his lonely atoll ever waited for mail more hopefully than does my craftsman writer when anticipating an advance against royalties or a check for his latest story.


In fact, mail call is the highlight of our day. My husband, Cris, who sometimes fails to hear entire paragraphs when I'm talking, can discern the mail truck's departure in town three and a half miles away, and provide minute by minute updates on its progress to our door.

In the early days, when we were struggling for a credit line on editorial mastheads, we sifted the day's haul eagerly for long, white, window envelopes. Since bills come in similar envelopes with discouraging regularity, gloom and doom often threatened to engulf us.

Our bills were an ongoing source of concern to Cris' mother, who wrung her hands and urged, "Speak to my son. Tell him to get a job!"

"He has a job," I would respond, gently but firmly. She would depart, shaking her head and clicking her rosary beads. I'm certain she had many sleepless nights when she realized her son had married a woman as custard-brained as himself.

With an older son well on his way up the corporate ladder, Cris' mother was challenged to search the family tree for a relative from whom Cris had inherited his improvident genes. My own mother, herself a risk-taker with a self-employed husband, told me, "Let him try," when, after the birth of our second son, Cris proposed quitting a highly paid job in an aircraft factory for full-time freelance writing. In the years that followed I vac-



LLUSTRATION BY RON BELL

illated, wondering whose mother's viewpoint would prevail.

Cris' lifelong romance with crafts and writing began long before our June marriage in the 1940s, and afforded our sons the benefit of a long apprenticeship. I learned to suppress my fears as the boys progressed from child-size tool sets and woodpile scraps to power tools and exotic woods. No wife or mother can view a dado assembly with equanimity when the fingers of her menfolk are in its path, and, conversely, no do-it-yourself partner can deny the pride of seeing those same men producing cabinets and furniture that rival the finest creations of old world artisans.

To free Cris for more production time, I edited and typed his copy. An eloquent

author and poet, Cris' syntax was perfect, but his spelling could only be described as, well, creative. We traded off baby-sitting and writing, and when I wasn't housekeeping or posing with projects he sold to editors, I wrote inspirational pieces and confessions for romance magazines. Such sales contributed to our budget, but were not frequent enough to offer solvency.

The plus side of having Cris at home-was having him on call 24 hours a day. I could tuck in our sons for afternoon naps, then go shopping and pity the harassed mothers who dragged howling toddlers through markets.


Still, as a do-it-yourselfer's housemate I learned to want what I had, rather than continued on p. 71

# Take the Stanley Book of Woodworking Frank and choose a second book Frank with a third for just \$1 plus postage and handling











#70230 160 pgs. Retail: \$24.95 #70249 144 pgs Retail: \$24.99 #70210 128 pgs. Pb. Retail: \$18.99 #70250 144 pgs. Pb. Retail: \$17.99 #70162 128 pgs. Retail: \$16.95 #70229 128 pgs. Pb. Retail: \$18.95





12 Professional

Finishing Secrets-

From Nick Engler.

A quick reference

guide that helps you identify, correct and

even avoid the most

common refinishing

joining now!

problems. A \$3.95 value,

it's yours FREE just for

YOURS FREE!



#70164 64 pgs. Retail: \$16.95

2 Professional

Faishing Secrets



112 pgs. Pb. Retail: \$14.95



#80212 245 pgs. Pb. Retail: \$24.95



144 pgs.




#80267 Retail: \$24.95



#80246 384 pgs. Pb. Retail: \$16.95



#70248 #80269 244 pgs. Pb. 144 pgs. Retail: \$22.99 Retail: \$18.95



#70209 160 pgs. Pb. Retail: \$19.95



#### SAVE TIME AND MONEY!

New! The Stanley Book of Woodworking Tools, Techniques and Projects is a onevolume resource packed with essential information you need from the world's leading manufacturer of hand tools.

A \$19.95 value, yours FREE as part of this membership offer.

#### As a member, you'll enjoy:

- Discounts from 15-50%
- Your FREE Bonus Book program
- FREE postage & handling (after this joining offer)
- Money-back Guarantee on every book you buy!

Membership Plan: Every 4 weeks, (14 times a year), you'll receive the NEWS describing the Main Selection and up to 100 more woodworking books. If you want the Main Selection, do nothing and it will be sent automatically. If you want a different book, or want nothing that month, you'll always have at least 10 days to decide and return your selection card. If late mail delivery ever causes you to receive a book you don't want, you may return it at club expense.

You are under NO OBLIGATION to buy any more books-you're just trying out the club for 6 months. After that, you may cancel at any time. Every time you buy a book from the Bulletin, your membership will be renewed for 6 months from the purchase date.

### MAIL THIS CERTIFICATE TODAY FOR YOUR BOOKS AND FREE GIFT!

MEMBERSHIP SAVINGS CERTIFICATE

| YES I want to join Woodworker's Book Club. I have read the M | fembership Plan | and understa | nd I have    |
|--|-----------------|--------------|--------------|
| NO OBLIGATION to buy any more books. Please send me:         | -               |              |              |
| The Stanley Book of Woodworking (#70264)                     | \$              | FREE         |              |
| and my FREE book selection #                                 | \$              | FREE         | MANAGE       |
| with my third selection book #                               |                 | 12.95        |              |
| plus my FREE 12 Professional Finishing Secrets #80174        | \$              | FREE         | The state of |
| add postage & handling costs                                 |                 | 5.61         | 10 mg        |
| All for the amoringly law mice of (total)                    | ¢               | 18 56        | 17           |

(Payment must accompany order. Ohio residents add 71¢ tax. Canadians add \$1.30 GST.)

| Acct #    | Charge my ☐ Visa ☐ MasterCard | Exp. L |
|-----------|-------------------------------|--------|
| Signature | 1.9                           |        |
| Name      | THE REAL PROPERTY.            |        |
| Address   | -                             |        |
|           | and the second second         |        |



P.O. Box 12171 Cincinnati, Ohio 45212-0171

Use your Visa or MasterCard to call TOLL-FREE 1-800-937-0963

9:00 a.m.-5:00 p.m. Eastern time, weekdays.

Offer good in U.S. and Canada for new members only. Remit in U.S. funds. Our numbers approve all applications and may cancel membership at any time. Please allow 3-4 weeks in household. The class reserves the right to

LAPO

If you prefer not to cut cover, please see extra coupon on page 60.

# IT HAS TWO SPEEDS: FASTER THAN YOU AND MUCH FASTER THAN YOU.

THE NEW DETAIL CARVER BY RYOBI.



While the human hand is a powerful tool, carving by hand can be painfully slow. That's why we created our new Detail Carver. It gives you hand-carved results – with power tool speed and ease. And you control all the power. The Detail Carver's ergonomic body, two speeds, and five interchangeable chisels let you quickly rough in and precisely finish off every carving project.

Relief carving. Incised carving. Sculpting.

Antique restoration. In every stock from apple to zebrawood. All with pinpoint finesse, in a fraction of the time hand carving takes. Yet the Detail

Carver costs no more than the hand carving sets it'll leave in the dust. Ryobi carves out another advance in power tool design. We've brought the fine art of hand carving up to speed.

Making Innovative Concepts A Reality"